#### 1. Services to be Furnished:

When and as ordered by the Contracting Officer (CO) or CO designee, the Contractor shall perform services consisting of testing samples of Government-owned petroleum products as described herein. Each geographical location for which testing is required, is identified by a Contract Line Item Number (CLIN). Each CLIN is further broken down into SubCLIN's to describe additional elements of service required for that location. The CLIN system is described in attachment 1.

When testing services are offered, which are not within commuting distance of the laboratory, the contractors price shall include the cost of transportation of samples to the laboratory.

The contractor should identify, in their offer, normal working hours and points of contact (names, addresses and phone numbers) for laboratories which will provide services under the contract. Additionally, hourly rate for working outside normal working hours (overtime), as well as expedite charges shall be provided as described further below.

The following attachments describe products to be tested, types of testing required and additional information as required:

Attachment No.	Product/Description
1	CLINs
2	JP-5 Specs
3	JP-8 Specs
4	Jet A/A1
5	F76 Specs
6	FSII
7	Sulfides
8	JPTS

NOTE: The quantities of samples for testing are <u>estimates only</u>. The services the Contractor shall be required to furnish and the Government to accept shall be those that, from time to time, may be ordered during the performance period of this contract.

#### 2. General:

The Defense Energy Support Center purchases, stores, and transports petroleum products to numerous Department of Defense activities. As part of our Quality Surveillance Program, we require samples to be submitted periodically. Testing is conducted to determine if product characteristics have changed as a result of method of transportation, length of storage and in some cases prior to discharge of marine vessels.

### 3. Description of Services:

- a. The contractor shall provide one or more laboratories capable of performing the tests associated with the products listed in the attachments referred to in paragraph 1 above. The laboratories shall have a system of calibration equivalent to ISO 10012-1 -- Quality Assurance Requirements for Measuring Equipment.
- b. The laboratory shall maintain an audit trail that will allow for identification of tests performed and specific equipment and technicians. All testing will be performed in strict accordance with test methods identified in attachments referred to in paragraph 1 above.
- c. Testing of U.S. Government-owned fuel products are required 24 hours per day, 7 days per week (including holidays). Under normal circumstances, samples will be received during contractor's normal working hours as set forth in the contract. However, should testing be required at other than normal working hours, such times are covered under Section 5. Samples shall be processed, tested, and results provided to the Quality Assurance Representative (QAR) identified below, within the prescribed turnaround times as indicated.

TURN AROUND TIMES	
B-1	24 hours
С	1 hour
Individual	8 hours
Accelerated Storage Stability	48 hours
Microbiological Growth	72 hours
Expedite	1 hour

Turn-around time is measured from the time the sample is taken (by the contractor when requested) to the time test results are received by the QAR or from the time samples are sent to the laboratory to the time test results are received by the QAR.

- d. The contractor shall maintain records evidencing all analysis performed under this contract. All samples tested will be documented with a detailed report which reflects standardized American Petroleum Institute / Institute of Petroleum (API/IP) format when available. The Contractor will telephone or fax test results to the QR and follow up with a hard copy by mail. Long distance phone charges, fax charges, and postage charges will not be reimbursed by the U.S. Government and should be included in testing prices.
- e. Samples shall be retained, after analysis, for a minimum of 15 days. In the event of a delivery dispute a longer sample retention period may be requested by DESC.
  - f. The Contractor shall be responsible for disposal of excess fuel sample and sample containers.
- g. Upon request of the QAR, the Contractor may be asked to provide Department of Transportation (DOT) approved sample containers and packaging/shipping materials. The Contractor is asked to quote a price under SERVICES TO BE FURNISHED above. The price should include transportation to the requesting QARs office.

### 4. Ordering of Services - Geographical Areas

Services are considered to be "ordered" when the Contractor's laboratory personnel receive the sample, along with instructions for which series/tests are to be performed. All orders are subject to the terms and conditions of the contract. Orders may be placed during the performance period of the contract.

Ordering of laboratory services shall be authorized by the DESC QAR assigned to the Defense Energy Support Region having cognizance over the location from which the samples originate, as follows:

#### (a) AREAS OF RESPONSIBILITY AND OFFICE CODES WITHIN THE CONTINENTAL UNITED STATES (CONUS):

Alabama	110	Maine	110	Oklahoma	110
Arizona	120	Maryland	110	Oregon	120
Arkansas	110	Massachusetts	110	Pennsylvania	110
California	120	Michigan	110	Rhode Island	110
Colorado	120	Minnesota	110	South Carolina	110
Connecticut	110	Mississippi	110	South Dakota	110
Delaware	110	Missouri	110	Tennessee	110
District of Columbia	110	Montana	120	Texas	110
Florida	110	Nebraska	110	Utah	120
Georgia	110	Nevada	120	Vermont	110
Idaho	120	New Hampshire	110	Virginia	110
Illinois	110	New Jersey	110	Washington	120
Indiana	110	New Mexico	120	West Virginia	110
Iowa	110	New York	110	Wisconsin	110
Kansas	110	North Carolina	110	Wyoming	120
Kentucky	110	North Dakota	110		
Louisiana	110	Ohio	110		

#### **EXCEPTIONS:**

- (1) The El Paso, Texas, area is assigned to Code 120 (DESC Americas West).
- (2) The Newcastle, Wyoming, area is assigned to Code 110 (DESC Americas East).

### (c) INSPECTION OFFICES AND CODES.

110. DESC Americas -- East

Federal Building, Room 1005

2320 LaBranch Street

Houston, TX 77004-1091

Phone: (713) 718-3883

FAX: (713) 718-3891

POC: Scott Artrip

email: scott.artrip@dla.mil

120. DESC Americas -- West

3171 N Gaffey Street

San Pedro, CA 90731-1099

Phone: (310) 900-6960 FAX: (310) 900-6973

POC: Michael Koury

email: michael.koury@dla.mil

### 5. Additional Services and Testing Outside Normal Working Hours

The Contractor shall perform such additional tests as the Contracting Officer (CO) or designated representative may require. The representative of the CO, for purposes detailed below, is hereby designated as the (QAR) of the Defense Fuel Region as assigned in Section 4.

The Contractor may be required to perform services at times other than the Contractor's normal working hours as set forth in this contract. When tests are requested and neither the CO nor the QAR are available, the Contractor may perform any reasonable tests as deemed necessary in order to make an adequate analysis of the samples of fuel furnished for testing. No additional tests that are beyond the Contractor's capability to perform shall be required.

Invoices for services performed under this clause shall be submitted in accordance with the Clause I1.03-1(g)--INVOICE, and this document. However, a separate certification will be required on the invoice citing those additional tests that were requested under this clause, and/or the amount of overtime required, and any resulting overtime charges.

Overtime is defined as the time outside the Contractors normal working hours when the sample has been placed in the normal queue. Expedite is defined as placing the sample at the front of the queue and performing the test immediately.

### 6. Testing in Support of Air Force One:

In accordance with paragraph 4 above, The Contractor shall perform testing on samples submitted in support of Air Force 1 (AF1). Samples submitted in support of (AF1) will be tested in accordance with the instructions provided at the time samples are submitted. A separate invoice will be prepared for AF1 support and submitted to DFAS per section 7.

#### 7. INVOICES:

- a. The contractor shall submit an invoice to the Quality Assurance Representative (QAR) of the Defense Energy Support Center as assigned in Section 4, for certification and authorization for payment. The invoice may be mailed, emailed or faxed to the QAR who will in turn forward a signed copy of the invoice to the contractor and DFAS for payment. A copy of the test results should not be sent to DFAS with the invoice. The Contractor shall prepare the invoice on the last day of each month. Each invoice shall contain the following information:
- (1) Contract number, CLIN, and SubCLIN
- (2) For each sample submitted:
  - Sample identification number
  - Sample date
  - Date testing is performed
  - Name and location of laboratory where testing is performed
  - List of tests performed and unit price for each
- (3) Total amount due on same line as Contract Line Item Number (CLIN).

b. Invoice shall be made out to:

DFAS-Columbus Center ATTN: DFAS-CVD-BBA-CC 3900 East Broad Street, Bldg 21 Columbus, Ohio 43213-1152

c. This invoicing procedure is interim and may be replaced by an automated procedure later.

### **CLIN and LOCATION LEGEND**

### **CLIN POSITION**

### **SubCLIN POSITION**

1 = Contract Year 1 = Contract Year

2 = Space Filler 2 = Service Requirement

3&4=Location 3 & 4 =Location 5 & 6 =Product Code

### **SERVICE REQUIREMENT**

A = Full-Specification Product Sample Testing

B = B-1 Series Sample Testing

C = C Series Sample Testing

D = B-2 Series Sample Testing

 $H = \underline{H}$  and blending Service. Volumetrically compositing fuel Samples taken from Barge/Tanker, or fuel samples with additives.

I = Individual Characteristic Sample Testing

K = Sampling Kits

O = Other

S = Tank Sampling Service of Product Identified at the Facility Identified

T = Transportation Service of Product Sample from the Identified Facility to the Laboratory

V = Vessel Sampling Service of Product Identified at the Facility Identified

#### PRODUCT CODES

CODE	PRODUCT
1	Jet A/Jet A-1
2	FSII
3	Bottom Water
4	JP-4
5	JP-5
6	F-76
7	O-250 (Lube / 17331)
8	JP-8
9	O-278 (Lube / 9000)
10	DF-1
11	DF-2
12	DF-A
13	DL-1
14	DL-2
15	DL-A
16	MUR
17	MUM
18	MUP
19	RFO
20	Hydraulic Fluids

CODE	PRODUCT
21	Lubricating Oils
22	Greases
23	FS-4
24	MGO
25	MGO (F76 SPEC)
26	COAL
27	IFO 180
28	IFO 380
29	JPTS
30	AVGAS
31	Diesel Fuel (Commercial)
32	Kerosene
33	
34	
35	
36	
37	
38	
39	
40	

### **LOCATION GUIDES**

### Continental United States (CONUS)

	CONTIG
	CONUS
00	One time testing any
	location CONUS
01	Baton Rouge, LA
02	Homestead, FL
03	Key West, FL
04	Lockhart, MS
05	Montgomery, AL
06	Moundville, AL
07	Moffett Field, CA
08	New York Harbor, NY
09	Selby, CA
10	Pt. Molate, CA
11	Salt Lake City, UT
12	Doraville, Bremen, GA
13	Port Everglades, FL
14	Houston, TX
15	Norwalk, CA
16	San Pedro, CA
17	Drumwright, OK
18	Aledo, TX
19	Baltimore, MD
20	Chicago, IL
21	San Antonio, TX
22	Corapolis, PA
23	Columbus, GA
24	Macon, GA
25	Selma, NC
26	Pratt & Whitney, Palm
	Beach, FL
27	Boston, MA
28	South Portland, ME
29	Alamogordo, NM
30	NAS Pensacola

CONUS		
31	Las Vegas	
32	Colton	
33	Norfolk, VA	
34	Groton, CT	
35	RIK	
36	Rapid City, SD	
37	Paulsboro, PA	
38	Pt. Mahon, DE	
39	Jacksonville, NJ	
40	Chelsea Mass	
41	Tampa FL	
42	Ludlow MA	
43	Andrews AFB MD	
44	Helena AL	
45	Abilene, TX	
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		

### **LOCATION GUIDES**

### Miscellaneous and Outside Continental US (OCONUS)

MISC LOCATIONS		
61	Coal Testing	
62	Bunker - Coast Guard	
63	Bunker - Navy	
64	Bunker - MSC	
65		
66		
67		
68		
69		
OC	CONUS LOCATIONS	
70	Ethiopia IP	
71	Senegal IP	
72	Ivory Coast IP	
73	Qatar	
74	Dubai, UAE	
75	Jebel Ali, UAE	
76	Yanbu, SA	
77	Ras Tanura, SA	
78	Muscat, Oman	
79	Bahrain	
80	Djbouti	
81	Pakistan	
82	Cypress IP	
83	Athens, GR	
84	Egypt	
85	Portugal IP	
86	Switzerland IP	
87	Austria IP	
88	Ankara Turkey	
89	Turkey	
90	Elazig, Turkey	
91	Diyarbakir, Turkey	
92	Batman, Turkey	
93	Malaty, Turkey	
94	Augusta Bay, Sicily	
95	Naples, IT	
96	Livorno, IT	
97	Cagliari, Sardinia	
98	Mersin, Turkey	
99	Antalya, Turkey	

OCONUS LOCATIONS		
A0	Iskenderun, Turkey	
A1	Al Dhafra	
A2	Adana, Turkey	
A3	Zaho, Iraq	
A4	Guam	
A5	Singapore	
A6	Hong Kong IP	
A7	Philippines IP	
A8	Australia	
A9	New Zealand IP	
В0	Panama/MGO	
B1	Kuwait	
B2	Greenland	
В3	Aden, Yemen	
B4	Fujairah UAE	
B5	Middle East	
В6	Iraq	
В7	Keamari	
В8	Chaklala	
B9		
C1		
C2		
C3		
C4		
C5		
C6		
C7		
C8		
C9		
D1		
D2		
D3		
D4		
D5		
D6		
D7		
D8		
D9		
E1		
E2		

# **TURBINE FUEL, AVIATION, GRADES JP-5 NATO F-44 TESTING REQUIREMENTS, MIL-DTL-5624 (Latest Version)**

- A. Full Specification Testing (A Series), includes the first 23 tests in the table below, provide one price for tests 1-23. Testing shall be performed in accordance with the specified test method.
- B. Individual tests or any combination of several tests maybe requested, provide individual prices for all tests listed below.

	CHARACTERISTIC	TEST METHOD, ASTM,
1	Workmanship	(2)
2	Color, Saybolt	D156 (1), D6045
3	Total Acid Number	D3242
4	Aromatics	D1319
5	Sulfur, Mercaptan, mass percent	D3227 (3)
6	Doctor Test	D4952 (3)
7	Sulfur, Total Percent	D1266, D2622, D3120, D4294 (1), or D5453
8	Distillation (4)	D86 (1), D2887
9	Flash Point (5)	D56, D93 (1), D3828
10	Density, or API Gravity	D1298, D4052 (1)
11	Freezing Point	D2386 (1), D5972
12	Viscosity at -20°C	D445
13	Heating Value, Net Heat of Combustion	D3338, D4809 (1), D4529
14	Cetane Index, Calculated (6)	D976, D4737
15	Hydrogen Content	D3701
16	Smoke Point	D1322
17	Copper Strip Corrosion	D130
18	Thermal Stability	D3241 (7)
19	Existent Gum	D381 (8)
20	Particulate Matter and Filtration Time (9) (10) (12)	D2276, D5452 (1)
21	Micro-separometer Rating	D3948
22	Fuel Systems Icing Inhibitor	D5006 (11)
23	Visual (Color)	NPA, Common Descriptive Terms (13)
24	Sulfides in Bottom Water	See Statement of Work (Attachment 3)
25	Copper (CU)	IP225 (14) (specific locations only)
26	Particulate Matter (9) (10)	D2276, D5452 (1)
27	Filtration Time	(12)
31	Karl Fisher Water	D6304 (Report a or c) (pertains to Apple Jelly)

### C. B-1 Series Testing (one price for the following 11 tests):

	CHARACTERISTIC
1	Workmanship
2	Color (Visual)
3	Distillation
4	Flash Point
5	Density or API Gravity
6	Freezing Point
7	Copper Strip Corrosion
8	Existent Gum
9	Particulate Matter (Solids)
10	Lead content (If contaminated with leaded fuels suspected)
11	Fuel Systems Icing Inhibitor

### D. B-2 Series Testing (one price for the following 14 tests):

	CHARACTERISTIC
1	Workmanship
2	Color (Visual)
3	Distillation
4	Flash Point
5	Density or API Gravity
6	Freezing Point
7	Copper Strip Corrosion
8	Existent Gum
9	Particulate Matter (Solids)
10	Lead content (If contaminated with leaded fuels suspected)
11	Fuel Systems Icing Inhibitor
12	Thermal Stability
13	Color, Saybolt
14	Total Acid Number

### E. Type C Testing (one price for the following 4 tests):

CHARACTERISTIC	
1	Workmanship
2	Color (Visual)
3	Distillation
4	Flash Point

#### NOTES:

- 1. Referee Test Method.
- 2. Workmanship; the fuel shall be clear and bright and visually free from undissolved water, sediment, or suspended matter. In case of dispute, the fuel shall be clear and bright at 21°C. Use particulate matter test methods listed herein to determine foreign matter content.
- 3. Perform Sulfur, Mercaptan test or Doctor test.
- 4. A condenser temperature of 0 to 4 °C (32 to 40 °F) shall be used for the distillation of JP-5 fuel.
- 5. ASTM D3828 may give results up to 1.7 °C below the ASTM D93 results. ASTM D56 may give results up to 1 °C below the ASTM D93 results.
- 6. Mid-boiling temperatures shall be obtained by either ASTM D86 or ASTM D2887 to perform the Cetane Index calculation. If ASTM D86 values are used, they shall be corrected to standard barometric pressure.
- 7. Thermal Stability test conditions and procedures for ASTM D3241
  - a. Minimum heater tube temperature at maximum point: 260 °C
  - b. Fuel system pressure: 3.45 MPa (500 psig)
  - c. Fuel flow rate: 3.0 mL/minute
  - d. Test duration: 150 minutes
- 8. If air is used instead of steam while performing ASTM D381, it shall be recorded. In case of a failure with air, the sample shall be retested using steam.
- 9. A minimum sample size of 3.79 liters (1 gallon) shall be filtered.
- 10. The flow reducer ring of Appendix paragraph A.3.c of MIL-DTL-5624, is not required.
- 11. Tests shall be performed with ASTM D5006 using the DiEGME scale of the refractometer.
- 12. The following procedure shall be used for the determination of Filtration Time and may be used to determine particulate matter as an alternate to ASTM D2276 or ASTM 5452.
- a. Membrane filters shall be removed from the package and placed in an oven for a minimum of 15 minutes at 90 °C. After preheating, but prior to weighing, the membrane filters shall be stored in a desiccator.
- b. Each membrane filter shall be weighed. A filter weighing in excess of 90 mg shall not be used in the test.
- c. The insert ring shall be centered on the filter base. One membrane filter shall be placed directly over the insert ring. The top funnel shall be locked into place.
- d. Immediately prior to filtering the fuel, shake the sample to obtain a homogenous mix and ensure that fuel temperature does not exceed 30 °C. Clean the exterior or top portion of the sample container to ensure no contaminants are introduced. Any free water present in the fuel sample will invalidate the filtration time results by giving an excessive filtration time rating.

- e. With the vacuum off, pour approximately 200 mL of fuel into the funnel.
- f. Turn vacuum on and record starting time. Continue filtration of the 3.79 liter sample, periodically shaking the sample container to maintain a homogenous mix. Record the vacuum in kPa (in. of mercury) 1 minute after start and again immediately prior to completion of filtration. Throughout filtration, maintain a sufficient quantity of fuel in the funnel so the membrane filter is always covered.
- g. Record the filtration time in minutes expressed to the nearest whole number. If filtration of the 3.79 liters is not completed within 30 minutes, the test will be stopped and the volume of the fuel filtered will be measured. In these cases, record filtration time as "greater than 30 minutes" and the total volume of fuel filtered.
- h. Record the vacuum in kPa (in. of mercury) as determined from the average of the two readings taken in A.6.1.f.
- i. After recording the filtration time, shut off the vacuum and rinse the sample container with approximately 100 mL of filtered petroleum ether and dispense into the filtration funnel. Turn on the vacuum and filter the 100 mL rinse. Turn off the vacuum and wash the inside of the funnel with approximately 50 mL of filtered petroleum ether. Turn on vacuum and filter. Repeat the funnel rinse with another 50 mL of petroleum ether but allow the rinse to soak the filter for approximately 30 seconds before turning on the vacuum to filter the rinse. With the vacuum on, carefully remove the top funnel and rinse the periphery of the membrane filter by directing a gentle stream of petroleum ether from the solvent dispenser from the edge of the membrane toward the center, taking care not to wash contaminants off the filter. Maintain vacuum after final rinse for a few seconds to remove the excess petroleum ether from the filter.
- j. Using forceps, carefully remove the membrane filter from the filter base and place in a clean Petri dish. Dry in the oven at 90 °C for 15 minutes with the cover on the Petri dish slightly ajar. Place dish in a dessicator and allow to cool for a minimum of 15 minutes. If more than one sample is processed, cooling time will have to be increased. Reweigh the filter.
- k. Record the total solids content in mg/liter by using the following formula:

Weight gain of filter in mgs = 
$$mg/liter$$
  
3.785

1. Should the sample exceed the 30-minute filtration time and a portion of the fuel is not filtered, the solids content in mg/liter will be filtered as follows: Determine the volume of fuel filtered by subtracting the ml of fuel remaining from 3.785.

m. Vacuum shall exceed 67.5 kPa (20 in. of mercury) throughout the test and fuel temperature shall be between 18 and 30°C.

- 13. Common Descriptive Terms; Water White, Light Straw, Straw, Prime White, Standard White, Lily White, Cream White. Changes in shade of fuel may indicate possible degradation of product.
- 14. Metals: Copper will be performed in accordance with IP-225, Determination of copper in light petroleum distillates Specrophotometric Method. Sensitivity: The laboratory must have the apparatus and expertise to enable them to perform the analysis and report results in the part per billion (PPB) range.

### TURBINE FUELS, AVIATION, KEROSENE TYPES, NATO F-34 (JP-8), NATO F-35, AND JP-8+100 TESTING REQUIREMENTS, MIL-DTL-83133 (LATEST VERSION)

- A. Full Specification Testing (A Series), includes the first 26 tests in the table below, provide one price for tests 1-26. Testing shall be performed in accordance with the specified test method.
- B. Individual tests or any combination of several tests maybe requested, provide individual prices for all tests listed below.

CHARACTERISTIC		TEST METHOD, ASTM
1	Workmanship	1/
2	Color, Saybolt	D156 2/ or D6045
3	Total Acid Number, mg KOH/gm	D3242
4	Aromatics	D1319
5	Sulfur, Total Percent	D129, D1266, D2622, D3120, D4294 2/ or
		D5453
6	Sulfur, Mercaptan	D3227
7	Doctor Test	D4952
8	Distillation 3/	D86 2/, D2887
9	Flash Point 4/	D56, D93 2/ or D3828
10	Density, or API Gravity	D1298 or D4052 2/, D1298
11	Freezing Point	D2386 2/, D5901 or D5972
12	Viscosity at -20°C	D445
13	Net Heat of Combustion, MJ/kg BTU/lb	D3338 5/ or D4809 2/
14	Hydrogen Content	D3701 2/, D3343
15	Smoke Point	D1322
16	Naphthalenes	D1840
17	Cetane Index, Calculated	D976 6/
18	Copper Strip Corrosion	D130
19	Thermal Stability	D3241 7/
20	Existent Gum	D381
21	Combined Test - Particulate Matter and Filtration Time 8/	D2276 or D5452 2/
22	Water Reaction, Interface Rating	D1094
23	Water Separation Index	D3948
24	Fuel Systems Icing Inhibitor	D5006 9/
25	Fuel Electrical Conductivity 10/	D2624
26	Color, Visual	NPA, Common Descriptive Terms 11/
27	Particulate Matter (Solids) 8/	D2276 or D5452 2/
28	Filtration Time	8/
29	Sulfides in Water	See Statement of Work (Attachment )
	Copper (CU)	IP225 12/ (specific locations only)
31	Karl Fisher Water	D6304 (Report a or c) (pertains to Apple
		Jelly)
32	Water - AEL or Aqua-Glo	AEL or Aqua-Glo Water Detector Kit

### C. B-1 Series Testing (one price for the following 14 tests):

	CHARACTERISTIC
1)	Workmanship
2)	Color (Visual)
3)	Distillation
4)	Flash Point
5)	Density or API Gravity
6)	Freezing Point
7)	Copper Strip Corrosion
8)	Existent Gum
9)	Particulate Matter (Solids)
10)	Filtration Time
11)	Water Reaction
12)	Water Separation Index
13)	Fuel Systems Icing Inhibitor
14)	Fuel Electrical Conductivity

### D. B-2 Series Testing (one price for the following 17 tests):

CHARACTERISTIC	
1) Workmanship	
2) Color (Visual)	
3) Distillation	
4) Flash Point	
5) Density or API Gravity	
6) Freezing Point	
7) Copper Strip Corrosion	
8) Existent Gum	
9) Particulate Matter (Solids)	
10) Filtration Time	
11) Water Reaction	
12) Water Separation Index	
13) Fuel Systems Icing Inhibitor	
14) Fuel Electrical Conductivity	
15) Thermal Stability	
16) Color, Saybolt	
17) Total Acid Number	

### E. Type C Testing (one price for the following 4 tests):

CHARACTERISTIC	
1) Workmanship	
2) Color (Visual)	
3) Density or API Gravity	
4) Flash Point	

F. Series for Air Force One Testing: (one price for the following 11 tests):

	CHARACTERISTIC		
1	1 Density, or API Gravity		
2	Distillation		
3	3 Freezing Point		
4	4 Flash Point		
5	5 Particulate Content		
6	6 Conductivity		
7	7 Copper Corrosion		
8	8 Water Reaction		
9	9 Existent Gum		
10	10 Fuel System Icing Inhibitor		
11	11 Water -AEL or Aqua-Glow		

#### **NOTES:**

1/ Workmanship; the fuel shall be clear and bright and visually free from undissolved water, sediment, or suspended matter. In case of dispute, the fuel shall be clear and bright at 21°C. Use particulate matter test methods listed in table 1 to determine foreign matter content.

2/ Referee Test Method.

3/A condenser temperature of  $0^{\circ}$  to  $4^{\circ}$  C ( $32^{\circ}$  to  $40^{\circ}$ F) shall be used for the distillation by ASTM D86.

4/ ASTM D56 may give results up to 1° C (2° F) below the ASTM D93 results. ASTM D3828 may give results up to 1.7° C (3° F) below the ASTM D93 results. Method IP170 is also permitted.

5/ When the fuel distillation test is performed using ASTM D2887, the average distillation temperature, for use in ASTM D3338 shall be calculated as follow: V = (10% + 50% + 95%)/3

6/ Mid-boiling temperature may be obtained by either *ASTM D86* or *ASTM D2887* to perform the cetane index calculation. *ASTM D86* values should be corrected to standard barometric pressure.

7/ Conduct test in accordance with ASTM D3241 visual heater tube rating reference Annnex A1.

Thermal Stability test conditions and procedures for ASTM D3241

a. Minimum heater tube temperature at maximum point: 260 °C

b. Fuel system pressure: 3.45 MPa (500 psig)

c. Fuel flow rate: 3.0 mL/minute d. Test duration: 150 minutes

After test completion; Remove the reservoir cover and pour into a measuring cylinder the fuel found above the piston only. If this measured fuel is less than 405 mls, the test must be repeated because insufficient fuel has been pumped for a normal 150-minute test. It is suggested to locate the cause of the insufficient flow before running another test.

The following data shall be reported:

- a. Differential pressure in millimeter of mercury at 150 minutes, or time to differential pressure of 25 millimeters of mercury, whichever comes first.
- b. Heater tube deposit visual code rating at the end of the test.
- c. If a Mark 8A tube deposit rater (TDR) is available, the maximum SPUN TDR rating shall be reported.
- 8/ A minimum sample size of 3.79 liters (1 gallon) shall be filtered. The following procedure shall be used for the determination of Filtration Time and may be used to determine particulate matter as an alternate to ASTM D2276 or ASTM 5452.
- a. Membrane filters shall be removed from the package and placed in an oven for a minimum of 15 minutes to 90° C. After preheating, but prior to weighing, the membrane filters shall be stored in a desiccator.
- b. Each membrane filter shall be weighed. A filter weighing in excess of 90 mg will not be used in the test
- c. The membrane filter shall be placed directly over the insert ring. The top funnel shall be locked into place.
- d. Immediately prior to filtering the fuel, shake the sample to obtain a homogeneous mix and assure that fuel temperature does not exceed 30° C (86° F). Clean the exterior or top portion of the sample container to ensure that no contaminants are introduced. Any free water present in the fuel sample will invalidate the filtration time results by giving an excessive filtration time rating.
- e. With the vacuum off, pour approximately 200 ml of fuel into the funnel.
- f. Turn vacuum on and record starting time. Continue filtration of the 3.79 liters (1 gallon) sample, periodically shaking the sample container to maintain a homogenous mix. Record the vacuum in kPa (inches of mercury) 1 minute after start and again immediately prior to completion of filtration. Throughout filtration, maintain a sufficient quantity of fuel in the funnel so that the membrane filter is always covered.
- g. Report the filtration time in minutes expressed to the nearest whole number. If filtration of the 3.79 liters (1 gallon) is not completed within 30 minutes, the test will be stopped and the volume of the fuel filtered will be measured. In these cases, report filtration time as ">30 minutes" and the total volume of fuel filtered.
- h. Report the vacuum in kPa (inches of mercury) as determined from the average of the two readings taken in *f*.
- i. After recording the filtration time, shut off the vacuum and rinse the sample container with approximately 100 ml of filtered petroleum ether and dispense into the filtration funnel. Turn the vacuum on and filter the 100 ml. Rinse. Turn vacuum off and wash the inside of the funnel with approximately 50 ml of filtered petroleum ether. Turn vacuum on and filter. Repeat the funnel rinse with another 50 ml of petroleum ether but allow the rinse to soak the filter for approximately 30 seconds before turning the vacuum on to filter the rinse. With vacuum on, carefully remove the top funnel and rinse the periphery of the membrane filter by directing a gentle stream of petroleum ether from the solvent dispenser from the edge of the membrane toward the center, taking care not to wash contaminants off the filter. Maintain vacuum after final rinse for a few seconds to remove the excess petroleum ether from the filter.

- j. Using forceps, carefully remove the membrane filter from the filter and place in a clean petri dish. Dry in the oven at 90° C (194° F) for 15 minutes with the cover on the petri dish slightly ajar. Place dish in a desiccator and allow to cool for a minimum of 15 minutes. If more than one sample is processed, cooling time will have to be increased. Reweigh the filter.
- k. Report the total solids content in mg/liter by using the following formula:

$$\frac{\text{Weight gain of filter in mgs}}{3.785} = \text{ mg/liter}$$

l. Should the sample exceed the 30-minute filtration time and a portion of the fuel is not filtered, the solids content in mg/liter will be figured as follows: Determine the volume of fuel filtered by subtracting the ml of fuel remaining from 3.785.

$$\frac{\text{Weight gain of filter in mgs}}{\text{ml of fuel filtered } X \text{ } 0.001} = \text{mg/liter}$$

- m. Vacuum shall exceed 67.5 kPa (20 in. of mercury) throughout the test and fuel temperature shall be between 18 and 30°C.
- 9/ Test shall be performed in accordance with ASTM D5006 using the DiEGME scale of the refractometer.
- 10/ Fuel at ambient tempature or 29.4C (85F) and lower.
- 11/ Common Descriptive Terms; Water White, Light Straw, Straw, Prime White, Standard White, Lily White, Cream White.
- 12/ Metals: Copper will be performed in accordance with IP-225, Determination of copper in light petroleum distillates Specrophotometric Method. Sensitivity: The laboratory must have the apparatus and expertise to enable them to perform the analysis and report results in the part per billion (PPB) range.

### AVIATION TURBINE FUEL, GRADE JET A/A1

### **TESTING REQUIREMENTS, ASTM D1655 (Latest Version)**

- A. Full Specification Testing (A Series), includes the first 20 tests in the table below, provide one price for tests 1-20. Testing shall be performed in accordance with the specified test method.
- B. Individual tests or any combination of several tests maybe requested, provide individual prices for all tests listed below.

CHARACTERISTIC		TEST METHOD, ASTM 1/
1	Workmanship, Finish, Appearance	1/
2	Color, Visual	2/
3	Total Acid Number	D3242
4	Aromatics	D1319
5	Sulfur, Mercaptan	D3227
6	Sulfur, Total Mass %	D1266, D2622, D4294, D5453
7	Distillation	D86 R/, D2887
8	Flash Point 3/	D56 R/, D3828
9	Density, or API Gravity	D1298, D4052
10	Freezing Point	D2386(R), D5972
11	Viscosity at –20°C	D445
12	Net Heat of Combustion 4/	D4529, D3338, D4809 R/
13	Smoke Point, mm	D1322
14	Naphthalenes	D1840
15	Copper Strip Corrosion	D130
16	JFTOT Thermal Stability 5/6/	D3241
17	Existent Gum	D381
18	Water Reaction, Interface Rating	D1094
19	Microseparometer Rating	D3948
20	Fuel Electrical Conductivity	D2624
21	Color, Saybolt	D156
22	Particulate Matter (Solids) 7/	D2276, D5452
23	Filtration Time	8/
24	Combined Test for Particulate and Filter Time 7/8/	D2276, D5452
25	Fuel Systems Icing Inhibitor	D5006
26	Sulfides in Water	See Statement of Work

**ATTACHMENT 4** 

### C. B-1 Series Testing (one price for the following 12 tests):

CHARACTERISTIC		
1) Workmanship		
2) Color (Visual)		
3) Distillation		
4) Flash Point		
5) Density or API Gravity		
6) Freezing Point		
7) Copper Strip Corrosion		
8) Existent Gum		
9) Particulate Matter (Solids)		
10) Lead content ( If contaminated with		
leaded fuels suspected)		
11) Water Reaction		
12) Fuel Systems Icing Inhibitor		

### D. B-2 Series Testing (one price for the following 15 tests):

CHARACTERISTIC
1) Workmanship
2) Color (Visual)
3) Distillation
4) Flash Point
5) Density or API Gravity
6) Freezing Point
7) Copper Strip Corrosion
8) Existent Gum
9) Particulate Matter (Solids)
10) Lead content ( If contaminated with
leaded fuels suspected)
11) Water Reaction
12) Fuel Systems Icing Inhibitor
13) Thermal Stability
14) Color, Saybolt
15 Total Acid Number

### E. Type C Testing (one price for the following 4 tests):

CHARACTERISTIC	
1) Workmanship	
3) Color (Visual)	
3) Density or API Gravity	
4) Flash Point	

F. Series for Air Force One Testing: (one price for the following 11 tests):

	CHARACTERISTIC		
1	1 Density, or API Gravity		
2	2 Distillation		
3	3 Freezing Point		
4	4 Flash Point		
5	5 Particulate Content		
6	6 Conductivity		
7	7 Copper Corrosion		
8			
9	9 Existent Gum		
10	10 Fuel System Icing Inhibitor		
11	11 Water -AEL or Aqua-Glow		

#### **NOTES:**

R/Referee Test Method

- 1/ Workmanship, Finish and Appearance Visually inspect fuel for undissolved water, sediment, and suspended matter. Note any nauseating or irritating odor.
- 2/ Common Descriptive Terms; Water White, Light Straw, Straw, Prime White, Standard White, Lily White, Cream White. Color shall be reported as an indicator of fuel quality. Reference X1.12.4 of D1655.
- 3/ Results obtained by Test Methods D 3828 may be up to 2°C lower than those obtained by Test Method D 56, which is the preferred method. In case of dispute, Test Method D 56 will apply.
- 4/ For all grades use either Eq 1 or Table 1 in Test Method D 4529 or Eq 2 in Test Method D 3338. Test Method D 4809 may be used as an alternative. In case of dispute, Test Method D 4809 shall be used.
- 5/(2.5) hours at controlled temperature of 260C, Preferred SI units are 3.3 kPa, max.
- 6/ Tube deposit ratings shall always be reported by the Visual Method; a rating by the Tube Deposit Rating (TDR) optical density method is desirable but not mandatory.
- 7/ Particulate Matter—Solid particulate contaminants such as dirt and rust shall be detected by filtration of the jet fuel through membrane filters under prescribed conditions. A minimum sample size of 3.79 liters (1 gallon) shall be filtered. The following procedure shall be used for the determination of Filtration Time and may be used to determine particulate matter as an alternate to ASTM D2276 or ASTM 5452.
- 8/ Filtration Time Test Procedure.

- a. Membrane filters shall be removed from the package and placed in an oven for a minimum of 15 minutes to 90° C. After preheating, but prior to weighing, the membrane filters shall be stored in a desiccator.
- b. Each membrane filter shall be weighed. A filter weighing in excess of 90 mg will not be used in the test.
- c. The membrane filter shall be placed directly over the insert ring. The top funnel shall be locked into place.
- d. Immediately prior to filtering the fuel, shake the sample to obtain a homogeneous mix and assure that fuel temperature does not exceed 30° C (86° F). Clean the exterior or top portion of the sample container to ensure that no contaminants are introduced. Any free water present in the fuel sample will invalidate the filtration time results by giving an excessive filtration time rating.
- e. With the vacuum off, pour approximately 200 ml of fuel into the funnel.
- f. Turn vacuum on and record starting time. Continue filtration of the 3.79 liters (1 gallon) sample, periodically shaking the sample container to maintain a homogenous mix. Record the vacuum in kPa (inches of mercury) 1 minute after start and again immediately prior to completion of filtration. Throughout filtration, maintain a sufficient quantity of fuel in the funnel so that the membrane filter is always covered.
- g. Report the filtration time in minutes expressed to the nearest whole number. If filtration of the 3.79 liters (1 gallon) is not completed within 30 minutes, the test will be stopped and the volume of the fuel filtered will be measured. In these cases, report filtration time as ">30 minutes" and the total volume of fuel filtered.
- h. Report the vacuum in kPa (inches of mercury) as determined from the average of the two readings taken in f.
- i. After recording the filtration time, shut off the vacuum and rinse the sample container with approximately 100 ml of filtered petroleum ether and dispense into the filtration funnel. Turn the vacuum on and filter the 100 ml. Rinse. Turn vacuum off and wash the inside of the funnel with approximately 50 ml of filtered petroleum ether. Turn vacuum on and filter. Repeat the funnel rinse with another 50 ml of petroleum ether but allow the rinse to soak the filter for approximately 30 seconds before turning the vacuum on to filter the rinse. With vacuum on, carefully remove the top funnel and rinse the periphery of the membrane filter by directing a gentle stream of petroleum ether from the solvent dispenser from the edge of the membrane toward the center, taking care not to wash contaminants off the filter. Maintain vacuum after final rinse for a few seconds to remove the excess petroleum ether from the filter.
- j. Using forceps, carefully remove the membrane filter from the filter and place in a clean petri dish. Dry in the oven at 90° C (194° F) for 15 minutes with the cover on the petri dish slightly ajar. Place dish in a desiccator and allow to cool for a minimum of 15 minutes. If more than one sample is processed, cooling time will have to be increased. Reweigh the filter.
- k. Report the total solids content in mg/liter by using the following formula:

Weight gain of filter in mgs = mg/liter3.785 l. Should the sample exceed the 30-minute filtration time and a portion of the fuel is not filtered, the solids content in mg/liter will be figured as follows: Determine the volume of fuel filtered by subtracting the ml of fuel remaining from 3.785.

## Weight gain of filter in mgs = mg/liter ml of fuel filtered X 0.001

- m. Vacuum shall exceed 67.5 kPa (20 in. of mercury) throughout the test and fuel temperature shall be between 18 and 30°C.
- 9/ Use the appropriate scale of the refractometer.
- 10/ Fuel at ambient temperature or 29.4C (85F) and lower.
- 11/ Metals: Copper will be performed in accordance with IP-225, Determination of copper in light petroleum distillates Specrophotometric Method. Sensitivity: The laboratory must have the apparatus and expertise to enable them to perform the analysis and report results in the part per billion (PPB) range.

### **FUEL, NAVY DISTILLATE NATO F-76**

### **TESTING REQUIREMENTS, MIL-F-16884 (Latest Version)**

- A. Full Specification Testing (A Series), includes the first 19 tests in the table below, provide one price for tests 1-19. Testing shall be performed in accordance with the specified test method.
- B. Individual tests or any combination of several tests maybe requested, provide individual prices for all tests listed below.

	CHARACTERISTIC	TEST METHOD, ASTM,
1	Appearance	D4176 (1)
2	Demulsification	D1401 (2)
3	Density or API Gravity	D1298 (R), D4052, D287
4	Distillation	D86 (3)
5	Cloud Point	D2500(R), D5771(4), D5772(4), D5773 (4), D6371 (5), IP309 (5), D4539(6)
6	Color (ASTM)	D1500 (R), D6045
7	Flash Point	D93
8	Particulate Contamination	D6217 (R), D5452 (7)
9	Pour Point	D97 (R), D5949 (8), D5950 (8)
10	Viscosity at 40°C	D445
11	Acid Number	D974 (R), D664
12	Ash	D482
13	Carbon Residue (10% Bottoms) (9)	D524 (R), D189, D4530
14	Copper Strip Corrosion	D130
15	Hydrogen Content	D4808 (R), D5291
16	Ignition Quality: Cetane Number or Cetane Index	D613 (R), D976
17	Storage Stability	D5304(R), D2274 (10)
18	Sulfur Content, wt. %	D4294 (R), D129, D1552, D2622
19	Trace Metals, (Calcium, Lead, Sodium plus Potassium, Vanadium)	D3605 (11)
20	Water & Sediment	D2709
21	Sulfides in Bottom Water	See Statement of Work (Attachment 3)

### A. B-1 Series Testing (one price for the following 7 tests):

CHARACTERISTIC				
1	Appearance			
2	Density or API Gravity			
3	Distillation			
4	Color			
5	Flash Point			
6	Particulate Contamination			
7	Carbon Residue			

### B. B-2 Series Testing (one price for the following 15 tests):

	CHARACTERISTIC			
1				
1	Appearance			
2	Density or API Gravity			
3	Distillation			
4	Cloud Point			
5	Color			
6	Flash Point			
7	Particulate Contamination			
8	Pour Point			
9	Viscosity at 40°C			
10	Storage Stability			
11	Carbon Residue (10% Bottoms)			
12	Copper Strip Corrosion			
13	Cetane Index			
14	Sulfur			
15	Water & Sediment by centrifuge			

### C. Type C Testing (one price for the following 4 tests):

CHARACTERISTIC		
1	Workmanship	
2	Density or API Gravity	
3	Color	
4	Flash Point	

### **NOTES:**

### (R) Referee Method

### Notes:

- (1) If the sample has no visible particulates, but is otherwise not "clear and bright" per ASTM D4176, procedure 1, then the product must be tested per ASTM D2709, to determine percent volume of water and sediment. If the sample fails ASTM D4176, procedure 1, because it contains visible sediment or particulate matter, product must be tested as per ASTM D5452 or ASTM D6217.
- (2) The demulsification test shall be conducted in accordance with ASTM D1401 with the following exceptions:
  - (a) Synthetic seawater in accordance with ASTM D1141 shall be the emulsifying fluid.
  - (b)The test temperature shall be 25 °C.
  - (c)The demulsification time shall be that required for separation into two layers with no visible cuff at the interface. A lacy emulsion or cuff which does not form a band shall be

- disregarded. The fuel/water/emulsion layer volumes shall be recorded at one-minute intervals and the demulsification time reported to the nearest minute.
- (3) As the end point of the distillation is approached, if either a thermometer reading of 385 °C or a decomposition point is observed, the heating shall be discontinued and the procedure resumed as directed in ASTM D86.
- (4) If either ASTM D5571, D5572, or D5573 is used, the temperature recorded in each respective test shall be rounded to the next lower integer and reported as the ASTM D2500 equivalent cloud point in accordance with ASTM D5771, D5772 or D5773.
- (5) This method may be used as a substitute if the test procedure is modified as follows: apply vacuum to the sample for the first time when the fuel sample temperature reaches –1 oC. If the time required for the 20 ml of fuel to be filtered through the wire mesh filter exceeds 60 seconds, record the test as a failure. If the time required for the 20-ml sample to flow through the filter is 60 seconds or less, record the test result as a pass. Do not repeat application of vacuum at successively lower temperatures. This is a modification of the requirement of ASTM D6371 (IP method 309) that vacuum be applied to the test specimen immediately after the test jar is inserted into the cooling jacket or, at a minimum, when the fuel is a least 5 oC above its cloud point.
- (6) Low Temperature Flow Test of ASTM D4539 may be used as a substitute method on the condition that the "specified test temperature" approach provided therein is used: start the test (apply the test vacuum to the test specimen for the first time) when the fuel sample temperature reaches −1 °C. Do not repeat application of vacuum at successive lower temperatures.
- (7) If ASTM D5452 is utilized, a one-liter minimum sample is required.
- (8) If either ASTM D5949 or D5950 is used, the results from these tests should be based on the observations at 3 °C temperature intervals and reported as the ASTM D97 equivalent.
- (9) When the finished fuel contains a cetane improver, the carbon residue requirement specified in Table I shall apply to the base fuel without the cetane improver.
- (10) If ASTM D2274 is utilized, the test period shall be extended from 16 hours to 40 hours.
- (11) Any quantitative spectroscopic method may be employed if correlation to ASTM D3605 is demonstrated to the satisfaction of the inspection authority.

#### FUEL SYSTEM ICING INHIBITOR / HIGH FLASH

### TESTING REQUIREMENTS, MIL-DTL-85470 (Latest Version), NATO S-1745

- A. Full Specification Testing (A Series), includes the 9 tests in the table below, provide one price for tests 1-9. Testing shall be performed in accordance with the specified test method.
- B. Individual tests or any combination of several tests maybe requested, provide individual prices for all tests listed below.

CHARACTERISTIC		TEST METHOD, ASTM	
1	Workmanship	0/	
2	Acid Number	D1613	
3	Color (Platinum Cobalt)	D1209 1/, E450	
4	Distillation	D1078	
5	Ethylene Glycol	2/	
6	pH of 25% Solution in Water	E70 3/	
7	Relative density (20°C / 20°C)	D891 1/4/, D4052	
8	Water (mass %)	D1364 /1, E1064, or E203	
9	Flash Point	D93 /1, D56, or D3828	

c. B-1 (one price for the following 6 tests):

CHARACTERISTIC		
1	Workmanship	
2	Distillation	
3	pH of 25% Solution in Water	
4	Relative density (20°C / 20°C)	
5	Water (% Weight)	
6	Flash Point	

c. B-2 (one price for the following 5 tests):

CHARACTERISTIC			
1	Workmanship		
2	Relative density (20°C / 20°C)		
3	Acid		
4	pH of 25% Solution in Water		
5	Water (% Weight)		

d. C Series Testing (one price for the following 4 tests):

CHARACTERISTIC			
1	Workmanship		
2	Relative Density (20°C / 20°C)		
3	Water (%, Weight		
4	Flash Point		

**ATTACHMENT 6** 

#### **NOTES:**

- 0/ Workmanship. Visually inspect the sample the inhibitor shall be uniform in quality, clear and bright, and free from suspended and foreign matter.
- 1/ Referee Test Method
- 2/ Ethylene glycol (percent by weight). The percent of ethylene glycol component in the diethylene glycol monomethyl ether shall be determined as below or ASTM-D4171 Annex A1 Test Method for etermining Purity of Fuel System Icing Inhibitors Using Ultra High Purity Ethylene Glycol Monomethyl Ether (anhydrous, 99.5+%) as the calibration standard for the analysis of diethylene glycol monomethyl ether.

Determination of Percent of Ethylene Glycol

<u>Reagents and materials</u>: Unless otherwise indicated, all reagents shall be American Chemical Society reagent grade or equivalent. Reference to water indicates distilled or deionized water.

- a. Oxidizing reagents: To a solution containing 5 grams of periodic acid (HIO4) or 5.9 grams of paraperiodic acid (HIO4  $\cdot$ 2H2O) in 200 milliliters (ml) of water, add 800 ml of glacial acetic acid. Store the solution in a dark, well-stoppered bottle.
- b. Potassium iodide: Twenty percent aqueous solution. Weigh out 20 grams of potassium iodide and dilute to 100 ml with distilled water.
- c. Sodium thiosulfate, standard 0.2N: Standardize weekly or before using by an accepted procedure.
  - d. Starch indicator solution: One percent aqueous.

#### Procedure:

- a. Pipette 100 ml of the oxidizing reagent into each of four 500 ml iodine flasks. Reserve two of the flasks for the blank determination.
- b. Introduce 15 grams of the sample, weighed to the nearest 0.1 gram, into each of two flasks and swirl to effect solution.
  - c. Allow the flasks to stand for 30 minutes at room temperature.
- d. While swirling, add 20 ml of 20 percent potassium iodide solution to each flask, in turn, immediately before titrating.
- e. Titrate the contents of each flask to a pale yellow color with standard 0.2N sodium thiosulfate. Add 2 ml of starch indicator and titrate to the disappearance of the blue color.
  - f. If the net titration is more than 20 ml, repeat the determination, using a smaller sample size.

#### Calculations:

Calculate the concentration of ethylene glycol as:

Weight percent ethylene glycol =  $(B-A) \times N \times 3.103$ 

(s)

#### Where:

A = ml of sodium thiosulfate required for the sample.

B = average ml of sodium thiosulfate required for the blank.

N = normality of sodium thiosulfate.

s = grams of sample.

- 3/ pH of 25 percent solution in water. Twenty-five ml of the inhibitor shall be pipetted into a 100 ml volumetric flask and filled with freshly boiled and cooled distilled water having a pH of 6.5 to 7.5. The pH value shall be measured with a pH meter calibrated in accordance with ASTM-E70. To avoid error caused by carbon dioxide in the air, the gas space over the solution shall be purged with carbon dioxide-free air.
- 4/ See ASTM D891, Method A or B.

#### TESTING FOR SULFIDES IN BOTTOM WATER

- (a) SCOPE. This method describes a procedure for determining the presence of hydrogen sulfide, which is sometimes formed as a result of bacterial action on the sulfates contained in water bottoms in fuel storage tanks.
- (b) APPARATUS. 250 ml conical flask.
- (c) MATERIALS.
- (1) Dilute (10%) chemically pure sulfuric or hydrochloric acid.
- (2) Lead acetate paper.
- (d) SAMPLES. Representative water samples from storage tank bottoms must be taken in a glass bottle. In some cases it will be necessary to take the water sample in a Bacon bomb sampler. Samples so taken will always be transferred to a glass bottle. To preclude oxidation by air, the filled bottle must be capped immediately. The sample should be tested as soon as possible after sampling to minimize possible changes in the composition of materials in the water.

### (e) PROCEDURE.

- (1) The sample must be shaken thoroughly just prior to performing the test to make certain that any sediment present is included in the portion of the sample to be tested.
- (2) Transfer 100 ml of the shaken sample into a conical flask. Add 20 ml of dilute (10%) chemically pure sulfuric or hydrochloric acid to the flask. Immediately place a piece of lead acetate paper folded in a "V" shape in the neck of the flask. Bring the water to a boil and continue to gently boil for three or four minutes.
- (f) REPORT. The presence of sulfides in the sample will be reported if the lead acetate paper shows a black or brown discoloration.

## TURBINE FUEL, AVIATION, THERMALLY STABLE TESTING REQUIREMENTS, MIL-DTL-25524 (LATEST VERSION)

- A. Full Specification Testing (A Series), includes all tests listed below (one price for all). Testing shall be performed in accordance with the specified test method.
- B. Individual tests are any one, or combination, of tests below (individual prices).

CHARACTERISTIC		Test Methods	
1	Workmanship	0/	
2	Color, Saybolt	1/ D156 or D6045	
3	Total acid number, mg KOH/g	D3242	
4	Aromatics, volume percent	D1319	
5	Sulfur, Mercaptan, mass percent OR	D3227	
6	Doctor Test	D4952	
7	Sulfur, total, mass percent	D1266, D2622, D3120, 1/ D4294, or D5453	
8	Distillation temperature, °C	/1 D86 or D2887	
10	Flash point, °C (°F)	D56, /1 D93, or /2 D3828	
11	Density, kg/L (API) at 15°C	D1298 or 1 D4052	
13	Freezing point, °C (°F)	1/ D2386, D5901 or D5972	
14	Viscosity, centistokes, at -40°C	D445	
15	Net heat of combustion, MJ/kg (BTU/lb)	D3338, D4529, or 3/ D4809	
17	Hydrogen content, mass percent OR	D3343 or 1/4/D3701	
18	Smoke point, mm	D1322	
19	Copper strip corrosion, 2 hr at 100°C	D130	
21	Thermal stability (JFTOT)	5/ D3241	
22	Existent gum, mg/100 mL	6/ D381	
23	Particulate Matter mg/L	7/ D2276 or 7/ D5452	
24	Water Reaction	D1094	
25	Water Separation	D3948	
26	Fuel system icing inhibitor, % vol	8/ D5006	

### C. B-1 Series Testing (one price for the following 14 tests):

CHARACTERISTIC		
1	Workmanship	
2	Color, Saybolt	
3	Distillation temperature	
4	Flash point	
5	Density, kg/L	
6	Freezing point,	
7	Copper strip corrosion,	
8	Thermal stability (JFTOT)	
9	Existent gum	
10	Particulate Matter	
11	Water Reaction	
12	Fuel system icing inhibitor	

### C. B-2 Series Testing (one price for the following 17 tests):

	CHARACTERISTIC
1) '	Workmanship
2) (	Color (Visual)
3) ]	Distillation
4) ]	Flash Point
5) ]	Density or API Gravity
6) ]	Freezing Point
7)	Copper Strip Corrosion
8) ]	Existent Gum
9) ]	Particulate Matter (Solids)
10)	Filtration Time
11) '	Water Reaction
12)	Water Separation Index
13) 1	Fuel Systems Icing Inhibitor
14) ]	Fuel Electrical Conductivity
15)	Thermal Stability
16)	Color, Saybolt
17)	Total Acid Number

D. Type C Testing (one price for the following 4 tests):

CHARACTERISTIC		
1	Workmanship	
2	Color, Saybolt	
3	Density, kg/L (API)	
4	Flash point	

#### NOTES:

0/ Workmanship. Visually inspect the fuel: clear, bright, and visually free from undissolved water, sediment, or suspended matter. In case of dispute, the fuel shall be clear and bright at 21°C (70°F).

#### 1/ Referee Test Method

- 2/ ASTM D56 may give results up to  $1^{\circ}$ C ( $2^{\circ}$ F) below the ASTM D93 results. ASTM D3828 may give results up to  $1.7^{\circ}$ C ( $3^{\circ}$ F) below the ASTM D93 results.
- 3/ For calculating the net heat of combustion using ASTM D3338, the average distillation temperature shall be calculated as follows, when the distillation is performed using ASTM D2887: V = ((10% + 50% + 90%)/3)
- 4/ For calculating the hydrogen content using ASTM D3343, the average distillation temperature shall be calculated as follows when the distillation is performed using ASTM D2887: V = ((10% + 50% + 90%) / 3)
- 5/ Thermal stability. The thermal stability test shall be conducted using ASTMD3241 (JFTOT).

Stability test conditions.

- a. Heater tube temperature at maximum point: 335°C (635°F)
- b. Fuel system pressure: 3.43 MPa (500 pounds/square inch of gravity)
- c. Fuel flow rate: 3.0 milliliter/minute
- d. Test duration: 150 minutes.

The heater tube shall be rated using the Alcor Mark 8A or Alcor Mark 9 Tube Deposit Rater (TDR)

a. Both before and after the JFTOT test, the heater tube shall be rated at 1 millimeter (mm) increments over the length of the heater tube that can be rated using the Alcor Mark 8A or Mark 9 TDR. The maximum increase in the TDR ratings (i.e., the maximum difference seen between the post-test and the pre-test TDR rating) shall be reported.

#### Report the following data

- a. Tube deposit TDR ratings.
- b. Differential pressure across the test filter.

- 6/ If air is used instead of steam while performing ASTM D381, it must be reported. In case of a failure with air, the sample must be retested using steam.
- 7/ A minimum sample size of 3.785 liters (1 gallon) shall be filtered.
- 8 Test shall be performed in accordance with ASTM D5006 or method 5327, 5340, or 5342 of FED-STD-791. Use the appropriate scale of the refractometer.

CLIN 0001 -	- Baton Roug	ge, LA			
Lab name and address:			Name of Lab Manager		
		• Lab	Phone Number		
		• Lab	Lab Fax Number		
Charge for	or working outs	side normal working hours (overtime): \$	per hour		
•	•	am pm Mon Fri.	·		
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	50	\$	
	JP8	B-2	0	\$	
	JP8	С	0	\$	
	JP8	Air Force One	UTE	\$	
	JP8	Individual	UTE	Ψ	
	31 0	Workmanship	OIL	\$	
		<u> •</u>			
		Color, Saybolt		\$	
		Total Acid Number, mg KOH/gm		\$	
		Aromatics		\$	
		Sulfur, Total Percent		\$	
		Sulfur, Mercaptan		\$	
		Doctor Test		\$	
		Distillation		\$	
		Flash Point		\$	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Net Heat of Combustion		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Naphthalenes		Φ.	
		Cetane Index, Calculated		\$ \$	
				\$ \$	
		Copper Strip Corrosion		Φ	
		Thermal Stability		<b>5</b>	
		Existent Gum		\$	
		Particulate Matter and Filtration Time	2	\$	
		Water Reaction, Interface Rating		\$	
		Water Separation Index		\$	
		Fuel Systems Icing Inhibitor		\$	
		Fuel Electrical Conductivity		\$	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$	
		Sulfides in Water		\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$	
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 62	Price per task \$	
	JP8	Vessel Sampling	0	\$	

**Note**: C-Testing and Sampling will be performed locally, in order to meet the 1 hour turnaround time requirement.

0

Tank Sampling

JP8

• Lab nam	e and address	• Name o	Name of Lab Manager	
		• Lab Pho	one Number	
		• Lab Fax	Number	
•	•	ide normal working hours (overtime): \$ am pm Mon. – Fri. Ex	•	
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Serie
	JP5	B-1	4	\$
	JP5	B-2	0	
	JP5	C	0	\$
	JP5	Individual	UTE	Ψ
	01.5	Workmanship	012	\$
		Color, Saybolt		\$
		Total Acid Number		\$
		Aromatics		\$ \$
		Sulfur, Mercaptan, mass percent		\$ \$
		Doctor Test		\$ \$
		Sulfur, Total Percent		Φ.
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$ \$
		Freezing Point		\$ \$
		Viscosity at -20°C		\$ \$
		Heating Value, Net Heat of Combustion		· ———
		Cetane Index, Calculated		\$
				Φ
		Hydrogen Content		<b>5</b>
		Smoke Point		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter		\$
		Filtration Time		\$
		Particulate Matter and Filtration Time		\$
		Micro-separometer Rating (11)		\$
		Fuel Systems Icing Inhibitor		\$
		Visual (Color)		\$
		Sulfides in Bottom Water		\$
		Copper (CU)		\$
<u>SubCLIN</u>	Product	<u>Task</u>	Est. Sample	Price per task
	JP5	Transportation	4	\$
	31 5	Transportation		Ψ

**Note**: C-Testing and Sampling will be performed locally, in order to meet the 1 hour turnaround time requirement.

0

Tank Sampling

JP5

Lab name and address:		S: • Nar	ne of Lab Manager	
		• Lab	Phone Number	
		• Lab	Fax Number	
Charge fo	r working outs	ide normal working hours (overtime): \$	per hour	
Normal w	orking hours <sub>-</sub>	am pm Mon Fri.	Except Holidays	
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	25	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	UTE	Ψ
	31 0	Workmanship	OIL	\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$ \$
		Aromatics		\$ \$
		Sulfur, Total Percent		\$ \$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		<b>5</b>
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration Time	e	\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$

<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 0	Price per task \$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

<b>CLIN</b>	0003	-Key	West,	FL
-------------	------	------	-------	----

Lab name and address:		Name of	Name of Lab Manager		
		• Lab Phoi	ne Number		
		• Lab Fax	Number		
		ide normal working hours (overtime): \$			
Normal	working hours _	am pm Mon Fri. Exc	ept Holidays		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP5	B-1	25	\$	
	JP5	B-2	0	\$	
	JP5	C	0	\$	
	JP5	Individual	UTE	+	
	01.5	Workmanship	012	\$	
		Color, Saybolt		\$ 	
		Total Acid Number		\$	
		Aromatics		\$	
		Sulfur, Mercaptan, mass percent		Ψ \$	
		Doctor Test		Ψ	
		Sulfur, Total Percent		Ψ	
		Distillation		Ψ ¢	
		Flash Point		Φ	
		Density, or API Gravity		Φ	
				<b>D</b>	
		Freezing Point		<b>5</b>	
		Viscosity at -20°C		<b>5</b>	
		Heating Value, Net Heat of Combustion		\$	
		Cetane Index, Calculated		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$	
		Existent Gum		\$	
		Particulate Matter		\$	
		Filtration Time		\$	
		Particulate Matter and Filtration Time		\$	
		Micro-separometer Rating (11)		\$	
		Fuel Systems Icing Inhibitor		\$	
		Visual (Color)		\$	
		Sulfides in Bottom Water		\$	
		Copper (CU)		\$	
<u>SubCLIN</u>	Product	<u>Task</u>	Est. Sample	Price per task	
	JP5	Transportation	0	\$	
	JP5	Vessel Sampling	0	\$	
	JP5	Tank Sampling	0	\$	

Lab name and address:		Name of Lab Manager		
			Lab Phone Number	
			Lab Fax Number	
Charge fo	r working outs	ide normal working hours (overt	ime): \$ per hour	
		am pn		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP5	B-1	15	\$
	JP5	B-2	0	\$
	JP5	C	0	\$
	JP5	Individual	UTE	· <u></u>
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number		\$
		Aromatics		\$
		Sulfur, Mercaptan, mass pe	ercent	\$
		Doctor Test		\$
		Sulfur, Total Percent		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Heating Value, Net Heat o	f Combustion	\$
		Cetane Index, Calculated		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter		\$
		Filtration Time		\$
		Particulate Matter and Filtr	ration Time	\$
		Micro-separometer Rating	(11)	\$
		Fuel Systems Icing Inhibite	or	\$

SubCLIN Product	<u>Task</u>	Est. Sample	Price per task
JP5	Transportation	15	\$
JP5	Vessel Sampling	0	\$
JP5	Tank Sampling	0	\$

Visual (Color)

Copper (CU)

Sulfides in Bottom Water

CLIN 0005	– Montgomei	ry, AL			
	ne and address	•	Name of Lab Manager		
		• Lab Pi	none Number		
		• Lab Fa	x Number		
Charge f	or working outs	side normal working hours (overtime): \$	per hour		
•	-	- , , ,	•		
Noman	working nours _	am pm Mon. – Fri. E	жсерт пошауѕ		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	25	\$	
	JP8	B-2	0	\$	
	JP8	C	0	\$	
	JP8	Air Force One	UTE	\$	
	JP8	Individual	UTE	Ψ	
	31 0	Workmanship	OIL	\$	
		Color, Saybolt		Φ.	
				·	
		Total Acid Number, mg KOH/gm		\$	
		Aromatics		<b>5</b>	
		Sulfur, Total Percent		\$	
		Sulfur, Mercaptan		\$	
		Doctor Test		\$	
		Distillation		\$	
		Flash Point		\$	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Net Heat of Combustion		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Naphthalenes		\$	
		Cetane Index, Calculated		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$	
		Existent Gum		\$	
		Particulate Matter and Filtration Time		\$	
		Water Reaction, Interface Rating		\$ \$	
		Water Separation Index		\$ \$	
				·	
		Fuel Systems Icing Inhibitor		\$	
		Fuel Electrical Conductivity		<b>5</b>	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$	
		Sulfides in Water		\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$	
SubCLIN	Product	<u>Task</u>	Est. Sample	Price per task	
	JP8	Transportation	25	\$	
	JP8	Vessel Sampling	0	\$	

0

Tank Sampling

JP8

CLIN 0006 – Moundville, AL	
Lab name and address:	Name of Lab Manager
	• I I DI - N - I

Lab Phone Number
Lab Fax Number

Charge for working outs	ide normal working hours	(overtime): \$	per hour
Normal working hours _	am	pm Mon. – Fi	ri. Except Holidays

SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	25	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual * See Below	UTE	
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$
		Aromatics		\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		<b>5</b>
		Karl Fisher Water		<b>5</b>
		Water - AEL or Aqua-Glo		<b>a</b>

<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 25	Price per task \$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

Lab name and address:		Name of Lab Manager		
			Lab Phone Number	
			Lab Fax Number	
•	•	side normal working hours (overtime	,	
Normal w	vorking hours .	am pm N	lon Fri. Except Holidays	
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	20	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	UTE	
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number, mg KOF	·I/gm	\$
		Aromatics		\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		\$
		Flash Point		<b>5</b>
		Density, or API Gravity		\$
		Freezing Point		\$ \$
		Viscosity at -20°C Net Heat of Combustion		\$ \$
		Hydrogen Content		\$ \$
		Smoke Point		\$ \$
		Naphthalenes		\$ \$
		Cetane Index, Calculated		\$ \$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtrati	ion Time	\$
		Water Reaction, Interface Ra		\$
		Water Separation Index	8	\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$

<u>SubCLIN</u>	Product JP8	$\frac{Task}{Transportation}$	Est. Sample 0	Price per task \$
	JP8	Vessel Sampling	0	\$
	IP8	Tank Sampling	0	\$

Lab name and address:		S: • Nam	Name of Lab Manager					
		• Lab	Phone Number					
		• Lab	Fax Number					
	Charge for working outside normal working hours (overtime): \$ per hour  Normal working hours am pm Mon Fri. Except Holidays							
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series				
	JP8 JP8 JP8 JP8	B-2 C Air Force One Individual * SEE BELOW Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity	4 0 UTE UTE * 135	\$				
		Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU) Karl Fisher Water Water - AEL or Aqua-Glo	* 225	\$ \$ \$ \$ \$				
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 0	Price per task \$				
	JP8	Vessel Sampling	0	\$				
	JP8	Tank Sampling	0	\$				

Lab name and address:		• Name of	Name of Lab Manager		
		• Lab Phor	ne Number		
		• Lab Fax	Number		
Charge f	for working outs	side normal working hours (overtime): \$	per hour		
Normal	working hours _	am pm Mon. – Fri. Exc	cept Holidays		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP5	B-1	18	\$	
	JP5	B-2	0	\$	
	JP5	C	0	\$	
	JP5	Individual *SEE BELOW	UTE	•	
		Workmanship		\$	
		Color, Saybolt		\$	
		Total Acid Number		\$	
		Aromatics		\$	
		Sulfur, Mercaptan, mass percent		Ψ	
		Doctor Test		Ψ	
		Sulfur, Total Percent		Φ	
		Distillation		Φ	
		Flash Point		<b>5</b>	
				<b>5</b>	
		Density, or API Gravity		<b>5</b>	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Heating Value, Net Heat of Combustion		\$	
		Cetane Index, Calculated		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability	* 3	\$	
		Existent Gum		\$	
		Particulate Matter		\$	
		Filtration Time		\$	
		Particulate Matter and Filtration Time		\$	
		Micro-separometer Rating (11)		\$	
		Fuel Systems Icing Inhibitor		\$	
		Visual (Color)		\$	
		Sulfides in Bottom Water		Φ.	
		Copper (CU)		\$	
		Karl Fisher Water	* 18	\$ \$	
SubCLIN	<u>Product</u>	Task	Est. Sample	Price per task	
	JP5	Transportation	0	\$	
	JP5	<del>-</del>	0	\$	
		Vessel Sampling			
	JP5	Tank Sampling	0	\$	

Lab name and address:			Name of Lab Manager		
		• Lab F	Phone Number		
		• Lab F	Fax Number		
		outside normal working hours (overtime): \$ urs am pm Mon Fri. E			
SubCLIN:		Type of Test	Est.Sample	Price per tests/Series	
	F76	B-1	18	\$	
	F76	B-2	4	\$	
	F76	C	0	\$	
	F76	Individual * SEE BELOW	UTE	¢	
		Appearance Demulsification		\$	
		Density or API Gravity		\$	
		Distillation		\$ \$	
		Cloud Point		\$ 	
		Color (ASTM)		\$	
		Flash Point	t	\$	
		Particulate Contamination		\$	
		Pour Point		\$	
		Viscosity @40C		\$	
		Acid Number		\$	
		Ash Carbon Residue (10% Bottoms)	=	<b>Ф</b>	
		Copper Strip Corrosion		φ \$	
		Hydrogen Content		\$ \$	
		Ignition Quality Cetane Number		\$	
		Ignition Quality Cetane Index		\$	
		Storage Stability	* 6	\$	
		Sulfur Content		\$	
		Trace Metals		\$	
		Water and Sediment	=	\$	
		Sulfides in Bottom Water	ſ	\$	
g 1 GY 77		m -	E. G.		
<u>SubCLIN</u>	Product	<u>Task</u>	Est. Sample	Price per task	
	F76	Transportation	0	\$	
	F76	Vessel Sampling	0	\$	
	F76	Tank Sampling	0	\$	

Lab name and address:		• Name	Name of Lab Manager		
			• Lab P	hone Number	
			• Lab F	ax Number	
_	_		ng hours (overtime): \$ pm Mon. – Fri. E		
Normai	working nou	is aiii -	piii won. – Fii. L	-xcept Holidays	
<b>SubCLIN</b>	<b>Product</b>	Type of Test		<b>Est.Sample</b>	Price per tests/Series
	FSII	A		0	\$
	FSII	B-1		22	\$
	FSII	C		0	\$
	FSII	Individual		UTE	
			Workmanship		\$
			Acid Number		\$
			Color (Platinum Cobalt)		\$
			Distillation		\$
			Ethylene Glycol		\$
		•	of 25% Solution in Water		\$
		Relativ	re density $(20^{\circ}\text{C} / 20^{\circ}\text{C})$		\$
			Water (mass %)		\$
			Flash Point		\$

<u>SubCLIN</u>	<b>Product</b>	<u>Task</u>	Est. Sample	Price per task
	FSII	Transportation	0	\$
	FSII	Vessel Sampling	0	\$
	FSII	Tank Sampling	0	\$

Lab nam	ne and addres	S: • Name	e of Lab Manager	
		• Lab I	Phone Number	
		• Lab I	Fax Number	
		side normal working hours (overtime): \$ am pm Mon Fri. I		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	0	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	405	Ψ
	31 0	Workmanship	403	\$
		Color, Saybolt		ው ፍ
		Total Acid Number, mg KOH/gm		\$ \$
		Aromatics		\$ \$
		Sulfur, Total Percent		Ф
		Sulfur, Mercaptan		\$ \$
		Doctor Test		Ф С
		Distillation		Ф
		Flash Point		Ф
		Density, or API Gravity		Ф
		•		φ \$
		Freezing Point		Φ
		Viscosity at -20°C Net Heat of Combustion		\$ \$
				\$ \$
		Hydrogen Content Smoke Point		· ———
				\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		<b>5</b>
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$
SubCLIN	Product	<u>Task</u>	Est. Sample	Price per task
	JP8	Transportation	0	\$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

• Lab name and address:		• Name of	Name of Lab Manager		
		Lab Phot	ne Number		
		• Lab Fax	Number		
-	-	de normal working hours (overtime): \$ am pm Mon. – Fri. Ex			
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Serie	
<del>Juo CEII (1</del>	JP5	B-1	0	-	
		B-1 B-2	_	\$	
	JP5	B-2 C	0	<b>5</b>	
	JP5		0	<b>\$</b>	
	JP5	Individual	400	ф	
		Workmanship		<b>5</b>	
		Color, Saybolt		\$	
		Total Acid Number		\$	
		Aromatics		\$	
		Sulfur, Mercaptan, mass percent		\$	
		Doctor Test		\$	
		Sulfur, Total Percent		\$	
		Distillation		\$	
		Flash Point		\$	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Heating Value, Net Heat of Combustion		\$	
		Cetane Index, Calculated		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$	
		Existent Gum		\$	
		Particulate Matter		\$	
		Filtration Time		Φ	
		Particulate Matter and Filtration Time		Ф	
		Micro-separometer Rating (11)		Ψ	
		Fuel Systems Icing Inhibitor		Φ	
				Ф Ф	
		Visual (Color)		Φ	
		Sulfides in Bottom Water		\$	
		Copper (CU)	¥ 10	\$	
		Karl Fisher Water	* 18	\$	
SubCLIN :	Product	<u>Task</u>	Est. Sample	Price per task	

Lab name and address:			Name of Lab Manager		
		•	Lab Phone Number		
		•	Lab Fax Number		
Charge fo	r working outs	ide normal working hours (overtime): \$_	per hour		
		am pm Mon			
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	18	\$	
	JP8	B-2	0	\$	
	JP8	C	0	\$	
	JP8	Air Force One	UTE	\$	
	JP8	Individual	UTE	<del></del>	
	010	Workmanship	012	\$	
		Color, Saybolt		\$	
		Total Acid Number, mg KOH/gm		\$	
		Aromatics	•	\$	
		Sulfur, Total Percent		\$	
		Sulfur, Mercaptan		\$	
		Doctor Test		\$ \$	
		Distillation		\$	
		Flash Point		Ф	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$ \$	
		Net Heat of Combustion		\$ \$	
				\$ \$	
		Hydrogen Content		:	
		Smoke Point		\$	
		Naphthalenes		\$	
		Cetane Index, Calculated		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$	
		Existent Gum	¥	\$	
		Particulate Matter and Filtration T	ıme	\$	
		Water Reaction, Interface Rating		\$	
		Water Separation Index		\$	
		Fuel Systems Icing Inhibitor		\$	
		Fuel Electrical Conductivity		\$	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$	
		Sulfides in Water		\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$	

<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 18	Price per task \$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

Lab name and address:		s:	Name of Lab Manager	
			Lab Phone Number	
			Lab Fax Number	
Charge fo	or working outs	side normal working hours (overtime	e): \$ per hour	
•	•	am pm M	·	
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	25	\$
	JP8	B-2	0	\$
	JP8	С	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	UTE	
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH	I/gm	\$
		Aromatics		\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtrati	on Time	\$
		Water Reaction, Interface Rat		\$
		Water Separation Index	C	\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$
				· ———————

<u>SubCLIN</u>	Product JP8	$rac{Task}{Transportation}$	Est. Sample 25	Price per task \$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

<b>CLIN</b>	0012 -	Doraville,	Breman.	GA

**FSII** 

• Lab nam	ne and addr	ess:	• Name	e of Lab Manager	
			• Lab F	Phone Number	
			• Lab I	ax Number	
_	_	utside normal working hours (			
SubCLIN	Product	Type of Test		Est.Sample	Price per tests/Series
	FSII	A		8	\$
	FSII	B-1		0	\$
	FSII	C		0	\$

C	0	\$
Individual	UTE	
Workmanship		\$
Acid Number		\$
Color (Platinum Cobalt)		\$
Distillation		\$
Ethylene Glycol		\$
pH of 25% Solution in Water		\$
Relative density (20°C / 20°C)		\$
Water (mass %)		\$
Flash Point		\$

<u>SubCLIN</u>	<b>Product</b>	<u>Task</u>	Est. Sample	Price per task
	FSII	Transportation	8	\$
	FSII	Vessel Sampling	0	\$
	FSII	Tank Sampling	0	\$

Lab nam	e and addres	S: • Name	of Lab Manager	
		• Lab Pf	none Number	
		• Lab Fa	x Number	
Charge fo	or working outs	side normal working hours (overtime): \$	per hour	
		am pm Mon. – Fri. E		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	6	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	UTE	Ψ
	31 0	Workmanship	CIL	\$
		Color, Saybolt		\$ \$
		Total Acid Number, mg KOH/gm		\$
		Aromatics		\$ \$
		Sulfur, Total Percent		\$ \$
		Sulfur, Mercaptan		\$ \$
		Doctor Test		Φ
		Distillation		Φ
				Φ
		Flash Point		Φ
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 6	Price per task

0

0

\$ \_\_\_\_\_

Vessel Sampling

Tank Sampling

JP8

JP8

#### CLIN 0014 - Houston, TX

• Lab name and address:	Name of Lab Manager
	Lab Phone Number
	Lab Fax Number
Charge for working outside normal working	hours (overtime): \$ ner hour

Charge for working outside normal working hours (overtime): \$\_\_\_\_\_ per hour Normal working hours \_\_\_\_\_ am - \_\_\_\_ pm Mon. - Fri. Except Holidays

<b>SubCLIN</b>	<b>Product</b>	Type of Test		Est.Sam	<u>ple</u>	Price per tests/Series
	FSII	A		4	ļ	\$
	FSII	B-1		(	)	\$
	FSII	C		(	)	\$
	FSII	Individual		(	)	
			Workmanship			\$
			Acid Number			\$
			Color (Platinum Cobalt)			\$
			Distillation			\$
			Ethylene Glycol			\$
		pН	of 25% Solution in Water			\$
		Relati	eve density $(20^{\circ}\text{C} / 20^{\circ}\text{C})$			\$
			Water (mass %)			\$
			Flash Point			\$

<u>SubCLIN</u>	Product	<u>Task</u>	Est. Sample	Price per task
	FSII	Transportation	0	\$
	FSII	Vessel Sampling	0	\$
	FSII	Tank Sampling	4	\$

CI	IN	001	4 -	Hor	iston,	TX
$\sim$ L	/II 1	vv	т —	1100	ioton.	1 4 1

Lab name and address:		Name of	Name of Lab Manager		
		• Lab Pho	ne Number		
		• Lab Fax	Number		
		ide normal working hours (overtime): \$ am pm Mon. – Fri. Ex			
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP5	B-1		\$	
	JP5	B-2	64	\$	
	JP5	C	0	\$	
	JP5	Individual	UTE		
		Workmanship		\$	
		Color, Saybolt		\$	
		Total Acid Number		\$	
		Aromatics		\$	
		Sulfur, Mercaptan, mass percent		\$	
		Doctor Test		\$	
		Sulfur, Total Percent		\$	
		Distillation		\$	
		Flash Point		\$	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Heating Value, Net Heat of Combustion		\$	
		Cetane Index, Calculated		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$ \$	
		Existent Gum		\$ 	
		Particulate Matter		\$ *	
		Filtration Time		\$	
		Particulate Matter and Filtration Time		\$	
		Micro-separometer Rating (11)		Ψ \$	
		Fuel Systems Icing Inhibitor		Ψ	
		Visual (Color)		Ψ	
		Sulfides in Bottom Water		Ψ	
		Copper (CU)		Φ	
		Karl Fisher Water		\$ \$	
SubCLIN	Product	<u>Task</u>	Est. Sample	Price per task	
	JP5	Transportation	0	\$	
	JP5	-	0	Φ.	
		Vessel Sampling		\$	
	JP5	Tank Sampling	64	\$	

## CLIN 0014 - Houston, TX

• Lab nan	ne and addi	ress: • Name	of Lab Manager	
		• Lab P	hone Number	
		• Lab F	ax Number	
		outside normal working hours (overtime): \$ ors am pm Mon Fri. E		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Serie
	F76 F76 F76	B-1 C Individual Appearance Demulsification Density or API Gravity Distillation Cloud Point Color (ASTM) Flash Point Particulate Contamination		\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$
		Particulate Containination Pour Point Viscosity @40C Acid Number Ash Carbon Residue (10% Bottoms) Copper Strip Corrosion Hydrogen Content Ignition Quality Cetane Number Ignition Quality Cetane Index		\$ \$ \$ \$ \$ \$ \$ \$ \$
		Storage Stability Sulfur Content Trace Metals Water and Sediment Sulfides in Bottom Water		\$ \$ \$ \$ \$
<u>SubCLIN</u>	Product F76 F76	<u>Task</u> Transportation Vessel Sampling	Est. Sample 0 0	Price per task  \$  \$  \$

CLIN	0014 -	Houston.	TX
------	--------	----------	----

Lab name and address:		S: • Name	Name of Lab Manager		
		• Lab F	Phone Number		
		● Lab F	<sup>2</sup> ax Number		
		side normal working hours (overtime): \$ am pm Mon Fri. E			
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU)	0 68 0 2 78	\$	
		Karl Fisher Water Water - AEL or Aqua-Glo		\$ \$	
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 0	Price per task \$	
	JP8	Vessel Sampling	40	\$	
	JP8	Tank Sampling	65	\$	

CI	IN	0012	1 - H	louston.	TX

• Lab name	e and address	• Name of	Lab Manager	
		• Lab Phor	ne Number	
		• Lab Fax	Number	
_	_	ide normal working hours (overtime): \$ am pm Mon Fri. Exc		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JPTS	B-1	0	\$
	JPTS	B-2	32	\$
	JPTS	C	49	\$
	<b>JPTS</b>	Individual	213	
		Workmanship		\$
		Color, Saybolt		\$
		Total acid number, mg KOH/g		\$
		Aromatics, volume percent		\$
		Sulfur, Mercaptan, mass percent		\$
		OR		
		Doctor Test		\$
		Sulfur, total, mass percent		\$
		Distillation temperature, °C		\$
		Flash point, °C (°F)		\$ 
		Density, kg/L (API) at 15°C		\$
		Freezing point, °C (°F)		\$
		Viscosity, centistokes, at -40°C		Ψ
		Net heat of combustion, MJ/kg		Ψ
		(BTU/lb)		Ψ
		Hydrogen content, mass percent OR		\$
		Smoke point, mm		\$
		Copper strip corrosion, 2 hr at		\$
		100°C		
		Thermal stability (JFTOT)		\$
		Existent gum, mg/100 mL		\$
		Particulate Matter mg/L		\$
		Water Reaction		\$
		Water Separation		\$
		Fuel system icing inhibitor, % vol		\$
SubCLIN	Product JPTS	<u>Task</u> Transportation	Est. Sample 0	Price per task \$
	JPTS	Vessel Sampling	4	\$
	JPTS		30	\$ \$
	JF 1 2	Tank Sampling	30	Φ

CI	IN	001	5 _	Norwa	alk	$C\Delta$
$\sim$ L	/II N	001	., —	I NUI W	air.	-

Lab name and address:		S: • Name	Name of Lab Manager		
		• Lab Pł	none Number		
		● Lab Fa	ıx Number		
		side normal working hours (overtime): \$ am pm Mon. – Fri. E			
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual * see below Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability * Special Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU) Karl Fisher Water Water - AEL or Aqua-Glo	120 0 0 UTE UTE	\$	
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample UTE	Price per task \$	
	JP8	Vessel Sampling	0	\$	
	JP8	Tank Sampling	0	\$	

CLIN 0015 – Norwalk, CA   • Lab name and address:  • Name of Lab Manager  • Lab Phone Number  • Lab Fax Number  Charge for working outside normal working hours (overtime): \$ per hour Normal working hours am pm Mon Fri. Except Holidays  SubCLIN: Product Type of Test  Est.Sample Price pe	
■ Lab Fax Number  Charge for working outside normal working hours (overtime): \$ per hour  Normal working hours am pm Mon Fri. Except Holidays	
Charge for working outside normal working hours (overtime): \$ per hour  Normal working hours am pm Mon Fri. Except Holidays	
Normal working hours am pm Mon Fri. Except Holidays	
<u>SubCLIN: Product Type of Test</u> <u>Est.Sample</u> <u>Price pe</u>	
<u> Duberna. Product Type of rest</u> <u>Est.painple</u> Trice pe	
JP5 B-1 120 \$	
JP5 B-2 0 \$	
JP5 C 0 \$	
JP5 Individual UTE	
Workmanship \$	
Color, Saybolt \$	
Total Acid Number \$	
Aromatics \$	
Sulfur, Mercaptan, mass percent \$	<del></del>
Do story Took	<del></del>
Sulfur, Total Percent \$	<del></del>
Distillation	<del></del>
Flash Point \$	
- · · · · · · · · · · · · · · · · · · ·	<del></del>
Viscosity at -20°C \$	<del></del>
Heating Value, Net Heat of Combustion \$	<del></del>
Cetane Index, Calculated \$	
Hydrogen Content \$	
Smoke Point \$	
Copper Strip Corrosion \$	
Thermal Stability \$	<del></del>
Existent Gum \$	
Particulate Matter \$	
Filtration Time \$	
Particulate Matter and Filtration Time \$	
Micro-separometer Rating (11) \$	
Fuel Systems Icing Inhibitor \$	
Visual (Color) \$	
Sulfides in Bottom Water \$	
C (CII)	
<u>SubCLIN</u> <u>Product</u> <u>Task</u> <u>Est. Sample</u> <u>Price per</u>	<u>task</u>
JP5 Transportation UTE \$	
JP5 Vessel Sampling 0 \$	<del></del>

Tank Sampling

JP5

CLIN 0016 - San Pedro, CA		
Lab name and address:	Name of Lab Manager	
	Lab Phone Number	
	Lab Fax Number	

Charge for working outside n	ormal working hour	rs (overtime): \$	per hour
Normal working hours	am -	nm Mon - Fri	Except Holidays

SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	A	2	\$
	JP8	B-1	100	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual - *See Below	100	
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$
		Aromatics		\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability *SPECIAL	100	\$
		Existent Gum		\$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$

<u>SubCLIN</u>	<u>Product</u>	<u>Task</u>	Est. Sample	Price per task
	JP8	Transportation	UTE	\$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

 $\textbf{Note} \hbox{:} \ \ C\text{-Testing and Sampling will be performed locally, in order to meet the 1 hour turn around time requirement.}$ 

Lab name	and address	s:	Name of Lab Manager	
			Lab Phone Number	
			Lab Fax Number	
_	_	ide normal working hours (overtime		
Normal w	orking hours _	am pm Mo	on Fri. Except Holidays	
SubCLIN:	<b>Product</b>	Type of Test	Est.Sample	Price per tests/Series
	JP5	A	2	\$
	JP5	B-1	60	\$
	JP5	B-2	0	
	JP5	C	0	\$
	JP5	Individual	UTE	
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number		\$
		Aromatics		\$
		Sulfur, Mercaptan, mass perce	ent	\$
		Doctor Test		\$
		Sulfur, Total Percent		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Heating Value, Net Heat of Co	ombustion	\$
		Cetane Index, Calculated		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter		\$
		Filtration Time		\$
		Particulate Matter and Filtration	on Time	\$

SubCLIN Product	<u>Task</u>	Est. Sample	Price per task
JP5	Transportation	UTE	\$
JP5	Vessel Sampling	0	\$
JP5	Tank Sampling	0	\$

Micro-separometer Rating (11) Fuel Systems Icing Inhibitor

Sulfides in Bottom Water

Visual (Color)

Copper (CU) Karl Fisher Water

Lab nan	ne and add	ress: • Name	of Lab Manager	
		• Lab P.	hone Number	
		• Lab F	ax Number	
		outside normal working hours (overtime): \$ pm Mon Fri. E		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	F76	A	2	\$
	F76	B-1	50	\$
	F76	C		\$
	F76	Individual		
		Appearance		\$
		Demulsification		\$
		Density or API Gravity		\$
		Distillation		\$
		Cloud Point		\$
		Color (ASTM)		\$
		Flash Point		\$
		Particulate Contamination		\$
		Pour Point		\$
		Viscosity @40C Acid Number		\$ \$
		Acid Number Ash		\$ \$
		Carbon Residue (10% Bottoms)		\$ \$
		Copper Strip Corrosion		\$
		Hydrogen Content		\$
		Ignition Quality Cetane Number		\$
		Ignition Quality Cetane Index		\$
		Storage Stability		\$
		Sulfur Content		\$
		Trace Metals		\$
		Water and Sediment		\$
		Sulfides in Bottom Water		\$
<u>SubCLIN</u>	Product	<u>Task</u>	Est. Sample	Price per task
	F76	Transportation	UTE	\$
	F76	Vessel Sampling	0	\$

0

Tank Sampling

F76

	<b>CLIN</b>	0016 -	- San	Pedro,	CA
--	-------------	--------	-------	--------	----

Lab name and address:		• Name	Name of Lab Manager		
			• Lab P	hone Number	
			• Lab F	ax Number	
_	_		ng hours (overtime): \$		
Normal	working hour	rs am	pm Mon. – Fri. E	Except Holidays	
SubCLIN	<b>Product</b>	Type of Test		Est.Sample	Price per tests/Series
	FSII	A		10	\$
	FSII	B-1		0	\$
	FSII	C		0	\$
	FSII	Individual		UTE	
			Workmanship		\$
			Acid Number		\$
			Color (Platinum Cobalt)		\$
			Distillation		\$
			Ethylene Glycol		\$
		pH	of 25% Solution in Water		\$
		Relati	ve density $(20^{\circ}\text{C} / 20^{\circ}\text{C})$		\$
			Water (mass %)		\$
			Flash Point		\$

<u>SubCLIN</u>	<u>Product</u>	<u>Task</u>	Est. Sample	Price per task
	FSII	Transportation	UTE	\$
	FSII	Vessel Sampling	0	\$
	FSII	Tank Sampling	0	\$

Lab name and address:		S: • Nar	Name of Lab Manager		
		• Lab	Phone Number		
		• Lat	Fax Number		
Charge fo	r working outs	ide normal working hours (overtime): \$	per hour		
Normal w	orking hours _	am pm Mon. – Fri	i. Except Holidays		
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	4	\$	
	JP8	B-2	0	\$	
	JP8	C	0	\$	
	JP8	Air Force One	UTE	\$	
	JP8	Individual	4		
		Workmanship		\$	
		Color, Saybolt		\$	
		Total Acid Number, mg KOH/gm		\$	
		Aromatics		\$	
		Sulfur, Total Percent		\$ \$	
		Sulfur, Mercaptan		Ψ	
		Doctor Test		Ψ	
		Distillation		φ	
				Φ	
		Flash Point		<b>5</b>	
		Density, or API Gravity		<b>5</b>	
		Freezing Point		<b>5</b>	
		Viscosity at -20°C		\$	
		Net Heat of Combustion		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Naphthalenes		\$	
		Cetane Index, Calculated		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$	
		Existent Gum		\$	
		Particulate Matter and Filtration Time	e	\$	
		Water Reaction, Interface Rating		\$	
		Water Separation Index		\$	
		Fuel Systems Icing Inhibitor		\$	
		Fuel Electrical Conductivity		\$	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$	
		Sulfides in Water		\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$ \$	

<u>SubCLIN</u>	<b>Product</b>	<u>Task</u>	Est. Sample	Price per task
	JP8	Transportation	UTE	\$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

CLIN 0017	_ Cushing	OK OR	DRIIMWR	IGHT	OΚ	2222222
CLIII OUI /	– Cusining,	OIX OIX	DICUMENT	TOIL	OIL	

Lab name and address:		• Name of	Name of Lab Manager		
		• Lab Pho	ne Number		
		• Lab Fax	Number		
		ide normal working hours (overtime): \$			
Normal	working hours _	am pm Mon. – Fri. Ex	cept Holidays		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP5	B-1	4	\$	
	JP5	B-2	0	\$	
	JP5	C	0	\$	
	JP5	Individual	2		
		Workmanship		\$	
		Color, Saybolt		\$	
		Total Acid Number		\$	
		Aromatics		\$	
		Sulfur, Mercaptan, mass percent		\$	
		Doctor Test		\$	
		Sulfur, Total Percent		\$	
		Distillation		\$ \$	
		Flash Point		\$	
		Density, or API Gravity		\$ \$	
		Freezing Point		\$	
		Viscosity at -20°C		\$ 	
		Heating Value, Net Heat of Combustion		\$ *	
		Cetane Index, Calculated		\$ 	
		Hydrogen Content		\$ *	
		Smoke Point		\$	
		Copper Strip Corrosion		\$ *	
		Thermal Stability		\$	
		Existent Gum		Ψ <b>¢</b>	
		Particulate Matter		\$	
		Filtration Time		\$	
		Particulate Matter and Filtration Time		\$ \$	
		Micro-separometer Rating (11)		Ψ <b>¢</b>	
		Fuel Systems Icing Inhibitor		Ψ <b>©</b>	
		Visual (Color)		Ф <b>С</b>	
		Sulfides in Bottom Water		\$ \$	
		Copper (CU)		\$	
SubCLIN	Product	<u>Task</u>	Est. Sample	Price per task	
	JP5	Transportation	UTE	\$	
	JP5	Vessel Sampling	0	\$	
	JP5		0		
	JPJ	Tank Sampling	U	\$	

CLIN	0019 –	Baltimore,	MD
------	--------	------------	----

Lab name and address:		S: • Nam	Name of Lab Manager				
		• Lab	Phone Number				
		• Lab	Fax Number				
	Charge for working outside normal working hours (overtime): \$ per hour  Normal working hours am pm Mon. – Fri. Except Holidays						
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series			
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU) Karl Fisher Water	30 0 UTE 20	\$			
SubCLIN	<u>Product</u>	Water - AEL or Aqua-Glo <u>Task</u>	<u>Est. Sample</u>	\$ Price per task			
Zuc CEII (	JP8	Transportation	30	\$			
	JP8	Vessel Sampling	0	\$			
	JP8	Tank Sampling	0	\$			

• Lab nan	ne and addres	s:	Name of Lab Manager	
			Lab Phone Number	
			Lab Fax Number	
•	•	ide normal working hours (overtime	•	
	-			D:
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	6	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	UTE	
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH	/gm	\$
		Aromatics	. 6	\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$ \$
		Distillation		\$ \$
		Flash Point		\$ \$
				Ф
		Density, or API Gravity		Φ
		Freezing Point		<b>5</b>
		Viscosity at -20°C		<b>5</b>
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration	on Time	\$
		Water Reaction, Interface Rat	ing	\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$ \$
		Karl Fisher Water		\$ \$
		Water - AEL or Aqua-Glo		\$ \$

 SubCLIN
 Product JP8
 Task Transportation
 Est. Sample Sample Sample Sample Sample Sample Sampling
 Price per task Sample Sam

Lab name and address:		Name of Lab Manager		
			Lab Phone Number	
			Lab Fax Number	
		de normal working hours (overtim		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Serie
		B-1	6	\$
	JETA/A1	B-2	0	\$
	JETA/A1	C	0	\$
	JETA/A1	Individual	UTE	
		Workmanship, Finish, Appe	earance	\$
		Color, Visual		\$
		Total Acid Number		\$
		Aromatics		\$
		Sulfur, Mercaptan		\$
		Sulfur, Total Mass %		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at –20°C		\$
		Net Heat of Combustion		\$
		Smoke Point, mm		\$
		Naphthalenes		\$
		Copper Strip Corrosion		\$
		JFTOT Thermal Stability		\$
		Existent Gum		\$
		Water Reaction, Interface R	ating	\$
		Microseparometer Rating		\$
		Fuel Electrical Conductivity	<i>!</i>	\$
		Color, Saybolt		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Particulate and Filter Time		\$
		Fuel Systems Icing Inhibitor	r	\$
		Sulfides in Water	-	\$ \$
		Samues in water		Ψ

SubCLIN Product	<u>Task</u>	Est. Sample	Price per task
JETA/A1	Transportation	0	\$
JETA/A1	Vessel Sampling	0	\$
JETA/A1	Tank Sampling	0	\$

	<ul> <li>Coraopolis,</li> <li>and addres</li> </ul>		of Lab Manager	
		• Lab Pho	one Number	
		• Lab Fa	x Number	
Charge fo	or working outs	ide normal working hours (overtime): \$	per hour	
Normal v	working hours _	am pm Mon Fri. Ex	cept Holidays	
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	A	2	\$
	JP8	B-1	5	\$
	JP8	B-2	0	\$
	JP8	C	Ö	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	5	¥ <u></u>
	<b>01</b> 0	Workmanship	3	\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$ <del></del>
		Aromatics		\$
		Sulfur, Total Percent		\$ <del></del>
		Sulfur, Mercaptan		\$
		Doctor Test		\$ <del></del>
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$ <del></del>
		Naphthalenes		\$ \$
		Cetane Index, Calculated		\$ \$
		Copper Strip Corrosion		\$ \$
		Thermal Stability		\$ \$
		Existent Gum		\$ \$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$ \$
		Water Separation Index		Φ.
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		Ф
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
				\$ \$
		Copper (CU) Karl Fisher Water		\$ \$
				\$ \$
		Water - AEL or Aqua-Glo		Φ
<u>SubCLIN</u>	<u>Product</u>	<u>Task</u>	Est. Sample	Price per task
	JP8	Transportation	12	\$
	JP8	Vessel Sampling	0	\$

0

Tank Sampling

JP8

CLIN 0023 – Columbus, GA	
Lab name and address:	Name of Lab Manager
	A V I DI V I

Lab Phone Number
Lab Fax Number

Charge for working outside normal working hours (overtime): \$\_\_\_\_\_ per hour Normal working hours \_\_\_\_\_ am - \_\_\_\_ pm Mon. - Fri. Except Holidays

SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	12	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	4	
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$
		Aromatics		\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$

<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 16	Price per task \$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

CLIN	0025 -	- DESP	Selma,	NC

Lab name and address:		S: • Nam	Name of Lab Manager		
		• Lab	Phone Number		
		• Lab	Fax Number		
		side normal working hours (overtime): \$ am pm Mon. – Fri.			
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU) Karl Fisher Water	14 0 0 UTE 14	\$	
<u>SubCLIN</u>	Product JP8	Water - AEL or Aqua-Glo <u>Task</u> Transportation	Est. Sample 0	Price per task \$	
	JP8	Vessel Sampling	0	\$	
	JP8	Tank Sampling	0	\$	

Lab name and address:		• N	Name of Lab Manager	
		• Li	ab Phone Number	
		• La	ab Fax Number	
Charge for	working outs	ide normal working hours (overtime): \$	per hour	
Normal we	orking hours _	am pm Mon Fr	i. Except Holidays	
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Serie
	JP5	B-1	15	\$
	JP5	B-2	0	\$
	JP5	C	0	\$
	JP5	Individual	14	T
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number		\$
		Aromatics		\$
		Sulfur, Mercaptan, mass percent		\$
		Doctor Test		\$
		Sulfur, Total Percent		Ψ
		Distillation		Ψ
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$ \$
		Viscosity at -20°C		
		Heating Value, Net Heat of Combus	ation	\$
		•	SHOII	\$
		Cetane Index, Calculated		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter		\$
		Filtration Time		\$
		Particulate Matter and Filtration Tin	ne	\$
		Micro-separometer Rating (11)		\$
		Fuel Systems Icing Inhibitor		\$
		Visual (Color)		\$
		Sulfides in Bottom Water		\$
		Daniacs in Bottom Water		Ψ

SubCLIN Product	<u> 1 ask</u>	Est. Sample	Price per task
JP5	Transportation	0	\$
JP5	Vessel Sampling	0	\$
JP5	Tank Sampling	0	\$

CLIN 0027 – Boston, M	ſΑ
-----------------------	----

Lab name and address:		S: • Name of	Name of Lab Manager      Lab Phone Number		
		• Lab Ph			
		• Lab Fa	x Number		
		ide normal working hours (overtime): \$ am pm Mon Fri. Ex			
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU) Karl Fisher Water Water - AEL or Aqua-Glo	6 0 UTE 6	\$	
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 6	Price per task \$	
	JP8	Vessel Sampling	0	\$	
	JP8	Tank Sampling	0	\$	

Lab name and address:		S: • Name of	Name of Lab Manager		
		• Lab Ph	one Number		
		• Lab Fa	x Number		
Charge f	or working outs	side normal working hours (overtime): \$	per hour		
Normal	working hours	am pm Mon Fri. Ex	ccept Holidays		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	17	\$	
	JP8	B-2	0	\$	
	JP8	C	0	\$	
	JP8	Air Force One	UTE	Ψ <b>©</b>	
	JP8	Individual	20	Ψ	
	JIO	Workmanship	20	\$	
		Color, Saybolt		\$ \$	
		•			
		Total Acid Number, mg KOH/gm		:	
		Aromatics		\$	
		Sulfur, Total Percent		\$	
		Sulfur, Mercaptan		\$	
		Doctor Test		\$	
		Distillation		\$	
		Flash Point		\$	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Net Heat of Combustion		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Naphthalenes		\$	
		Cetane Index, Calculated		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$	
		Existent Gum		\$	
		Particulate Matter and Filtration Time		\$	
		Water Reaction, Interface Rating		\$	
		Water Separation Index		\$	
		Fuel Systems Icing Inhibitor		\$	
		Fuel Electrical Conductivity		\$	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$	
		Sulfides in Water		\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$	
		The of rique of		Ψ	
<u>SubCLIN</u>	Product	Task	Est. Sample	Price per task	

<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 0	Price per task \$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

Lab nam	ne and addres	S: • Name o	of Lab Manager	
		• Lab Ph	one Number	
		• Lab Fa:	x Number	
Charge f	or working outs	side normal working hours (overtime): \$	per hour	
Normal	working hours	am pm Mon Fri. Ex	cept Holidays	
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	70	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	20	Ψ
	31 0	Workmanship	20	\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$
		Aromatics		\$ \$
		Sulfur, Total Percent		\$ \$
		Sulfur, Mercaptan		\$ \$
		Doctor Test		\$ \$
		Distillation		\$ \$
		Flash Point		· <del></del>
				\$ \$
		Density, or API Gravity		\$ \$
		Freezing Point		Φ
		Viscosity at -20°C		Ф Ф
		Net Heat of Combustion		<b>Ф</b>
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$
<u>SubCLIN</u>	Product	<u>Task</u>	Est. Sample	Price per task
			2	_

 JP8
 Transportation
 0
 \$\_\_\_\_\_\_

 JP8
 Vessel Sampling
 0
 \$\_\_\_\_\_\_

 JP8
 Tank Sampling
 0
 \$\_\_\_\_\_\_

Lab name and address:		S: • Nam	Name of Lab Manager		
		• Lab	Phone Number		
		• Lab	Fax Number		
•	-	side normal working hours (overtime): \$	•		
Normal	working hours	am pm Mon Fri.	Except Holidays		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	0	\$	
	JP8	B-2	0	\$	
	JP8	C	0	\$	
	JP8	Air Force One	UTE	\$ \$	
	JP8	Individual	100	Ψ	
	31 0	Workmanship	100	\$	
		Color, Saybolt		\$	
		Total Acid Number, mg KOH/gm		\$	
		Aromatics		\$	
		Sulfur, Total Percent		\$	
		Sulfur, Mercaptan		\$ \$	
		Doctor Test		\$	
		Distillation		\$	
		Flash Point		\$ \$	
		Density, or API Gravity		\$ \$	
		Freezing Point		\$ \$	
		Viscosity at -20°C		\$ \$	
		Net Heat of Combustion		\$ \$	
		Hydrogen Content		¢	
		Smoke Point		Φ.	
				¢	
		Naphthalenes		· <del></del>	
		Cetane Index, Calculated		\$ \$	
		Copper Strip Corrosion		: <del></del>	
		Thermal Stability Existent Gum		\$	
		Particulate Matter and Filtration Time		\$ \$	
		Water Reaction, Interface Rating	;		
				\$	
		Water Separation Index		\$	
		Fuel Systems Icing Inhibitor		\$	
		Fuel Electrical Conductivity		\$	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$	
		Sulfides in Water		\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$	
SubCLIN	Product IP8	<u>Task</u> Transportation	Est. Sample 100	Price per task	
	IPX	i ranchortation	1 ( )( )	\$	

<u>SubCLIN</u>	<b>Product</b>	<u>Task</u>	Est. Sample	Price per task
	JP8	Transportation	100	\$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

CI	IN	0032	<ul> <li>Colton.</li> </ul>	Nevac	la
$\sim$ L	ALL N	0034	– Conton	. INEVac	ıа

Lab name and address:		S: • Name o	Name of Lab Manager      Lab Phone Number		
		• Lab Ph			
		• Lab Fa	x Number		
		side normal working hours (overtime): \$ am pm Mon. – Fri. E			
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	6	\$	
	JP8	B-2	0	\$	
	JP8	C	0	\$	
	JP8	Air Force One	UTE	\$	
	JP8	Individual	4	<del></del>	
	01 0	Workmanship	·	\$	
		Color, Saybolt		\$	
		Total Acid Number, mg KOH/gm		\$	
		Aromatics		\$	
		Sulfur, Total Percent		\$	
		Sulfur, Mercaptan		\$	
		Doctor Test		\$	
		Distillation		\$	
		Flash Point		\$	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Net Heat of Combustion		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Naphthalenes		\$ \$	
		Cetane Index, Calculated		\$ \$	
		Copper Strip Corrosion		Ψ	
		Thermal Stability		\$ \$	
		Existent Gum		\$ \$	
		Particulate Matter and Filtration Time		• ————	
		Water Reaction, Interface Rating		\$ \$	
		Water Separation Index		\$ \$	
		Fuel Systems Icing Inhibitor			
		Fuel Electrical Conductivity		\$	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$ \$	
		Sulfides in Water			
				\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$	
SubCLIN	<u>Product</u>	<u>Task</u>	Est. Sample	Price per task	
	JP8	Transportation	10	\$	
	JP8	Vessel Sampling	0	\$	
		• •			
	JP8	Tank Sampling	0	\$	

CLIN 0055 - Nolloik, VA							
Lab name and address:	Name of Lab Manager						

CLIN 0033 - Norfork, VA	
Lab name and address:	Name of Lab Manager
	Lab Phone Number
	Lab Fax Number
Charge for working outside normal working	hours (overtime): \$ per hour
Normal working hours am	pm Mon Fri. Except Holidays

SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	10	\$
	JP8	B-2	0	\$
	JP8	С	2	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	UTE	
		Workmanship	-	\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$
		Aromatics		\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$
		1		•
SubCLIN	Product	Task	Est. Sample	Price per task

<b>SubCLIN</b>	<b>Product</b>	<u>Task</u>	Est. Sample	Price per task
	JP8	Transportation	0	\$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

## CLIN 0033 - Norfork, VA

Lab name and address:		• Name of	Name of Lab Manager				
		• Lab Pho	ne Number				
		• Lab Fax	Number				
	Charge for working outside normal working hours (overtime): \$ per hour  Normal working hours am pm Mon Fri. Except Holidays						
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series			
	JP5	B-1	10	\$			
	JP5	B-1	0	\$			
	JP5	B-2	0	\$			
	JP5	C	2	\$			
	JP5	Individual	UTE	Ψ			
	31 3	Workmanship	OIL	<b>¢</b>			
		Color, Saybolt		\$			
		Total Acid Number		Ф			
		Aromatics		Φ			
				<b>4</b>			
		Sulfur, Mercaptan, mass percent		<b>5</b>			
		Doctor Test		\$			
		Sulfur, Total Percent		\$			
		Distillation		\$			
		Flash Point		\$			
		Density, or API Gravity		\$			
		Freezing Point		\$			
		Viscosity at -20°C		\$			
		Heating Value, Net Heat of Combustion		\$			
		Cetane Index, Calculated		\$			
		Hydrogen Content		\$			
		Smoke Point		\$			
		Copper Strip Corrosion		\$			
		Thermal Stability		\$			
		Existent Gum		\$			
		Particulate Matter		\$			
		Filtration Time		\$			
		Particulate Matter and Filtration Time		\$			
		Micro-separometer Rating (11)		\$			
		Fuel Systems Icing Inhibitor		\$			
		Visual (Color)		\$			
		Sulfides in Bottom Water		Φ			
		Copper (CU)		\$ \$			
		Karl Fisher Water		\$			
<u>SubCLIN</u>	Product	<u>Task</u>	Est. Sample	Price per task			
<u> </u>	JP5	Transportation	0	\$			
	JP5	_	0	\$			
		Vessel Sampling					
	JP5	Tank Sampling	0	\$			

## CLIN 0033 - Norfork, VA

Lab name and address:		• Name	Name of Lab Manager		
			• Lab Pl	hone Number	
			• Lab Fa	ax Number	
		outside normal working hours (c			
SubCLIN:	Product	Type of Test		Est.Sample	Price per tests/Series
	F76 F76 F76	Particulate O  Vi  Carbon Residue ( Copper S Hyd Ignition Quality O Ignition Quality St	trip Corrosion rogen Content etane Number		\$
<u>SubCLIN</u>	Product F76 F76	<u>Task</u> Transportat Vessel Samp	oling	Est. Sample 0 0	<u>Price per task</u> \$ \$
	F76	Tank Sampl	ing	0	\$

• Lab name	e and addres		ame of Lab Manager	
			ab Phone Number	
			ab i none rumbei	
		• L	ab Fax Number	
Charge fo	or working outs	side normal working hours (overtime): \$	per hour	
Normal w	vorking hours <sub>-</sub>	am pm Mon F	ri. Except Holidays	
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	A	4	\$
	JP8	B-1	36	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual		
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$
		Aromatics		\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration Tir	me.	\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$ 
		Fuel Electrical Conductivity		Φ.
		Color, Visual		Φ.
		Particulate Matter (Solids)		Φ.
		Filtration Time		\$ \$
		Sulfides in Water		·
				·
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$

<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 40	Price per task \$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

CLIN	0037	- Paulsboro.	NJ

Lab name and address:		S: • Name	Name of Lab Manager		
		• Lab P	hone Number		
		• Lab F	ax Number		
		side normal working hours (overtime): \$ am pm Mon Fri. E			
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual * see below Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water	36 0 0 UTE 36	\$	
		Copper (CU) Karl Fisher Water Water - AEL or Aqua-Glo	* 36	\$ \$ \$	
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 0	Price per task	
	JP8	Vessel Sampling	0	\$	
	JP8	Tank Sampling	0	\$	

(	CI	IN	0038	_ Pt	Mahon	DE

• Lab nan	ne and addres	• Na	me of Lab Manager	
		• La	b Phone Number	
		• La	b Fax Number	
		side normal working hours (overtime): \$ am pm Mon Fri		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Tim Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU) Karl Fisher Water Water - AEL or Aqua-Glo	4 0 UTE UTE	\$
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 0	Price per task \$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$

CLIN 0039 - Ja	icksonville, NJ
----------------	-----------------

Lab name and address:		S: • Name	Name of Lab Manager		
		• Lab I	Phone Number		
		• Lab I	Fax Number		
		side normal working hours (overtime): \$ am pm Mon Fri. I			
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU)	4 0 UTE UTE	\$	
		Karl Fisher Water Water - AEL or Aqua-Glo		\$	
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 0	Price per task \$	
	JP8	Vessel Sampling	0	\$	
	JP8	Tank Sampling	0	\$	

	– DESP Tam ne and addres		of Lab Manager	
		• Lab Pf	none Number	
		• Lab Fa	x Number	
Charge t	for working outs	ide normal working hours (overtime): \$	per hour	
Normal	working hours _	am pm Mon. – Fri. E	xcept Holidays	
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	14	\$
	JP8	B-2	0	\$
	JP8	C	0	\$
	JP8	Air Force One	UTE	\$
	JP8	Individual	14	Ψ
	<b>01</b> 0	Workmanship	1.	\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$ *
		Aromatics		\$
		Sulfur, Total Percent		\$ *
		Sulfur, Mercaptan		\$ *
		Doctor Test		\$
		Distillation		\$ *
		Flash Point		\$ \$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$ \$
		Hydrogen Content		\$ \$
		Smoke Point		\$ \$
		Naphthalenes		Ψ
		Cetane Index, Calculated		\$ \$
		Copper Strip Corrosion		\$ \$
		Thermal Stability		\$ \$
		Existent Gum		\$ \$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		Ψ <b>¢</b>
		Fuel Electrical Conductivity		Ψ <b>¢</b>
		Color, Visual		\$ \$
		Particulate Matter (Solids)		\$ \$
		Filtration Time		\$ \$
		Sulfides in Water		·
				\$
		Copper (CU) Karl Fisher Water		\$
				\$ \$
		Water - AEL or Aqua-Glo		Φ
<u>SubCLIN</u>	<u>Product</u>	<u>Task</u>	Est. Sample	Price per task
_ == CDII (	JP8	Transportation	0	\$

0

Vessel Sampling

Tank Sampling

JP8

JP8

Lab name	e and address	• Name	e of Lab Manager	
		• Lab I	Phone Number	
		• Lab I	Fax Number	
		ide normal working hours (overtime): \$ am pm Mon. – Fri.		
SubCLIN:	Product		Est.Sample	Price per tests/Serie
	JP5	B-1	15	\$
	JP5	B-2	0	\$
	JP5	C	0	\$ \$
	JP5	Individual	14	Ψ
	31 3	Workmanship	14	\$
		Color, Saybolt		\$ \$
		Total Acid Number		ф
		Aromatics		Φ.
		Sulfur, Mercaptan, mass percent		Φ.
		Doctor Test		Φ.
		Sulfur, Total Percent		Φ.
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$ \$
		Freezing Point		Φ
		Viscosity at -20°C		Φ.
		Heating Value, Net Heat of Combustion	on	¢
		Cetane Index, Calculated	)II	<b>C</b>
		Hydrogen Content		Φ.
		Smoke Point		Φ.
		Copper Strip Corrosion		Φ.
		Thermal Stability		\$
		Existent Gum		\$
				\$
		Particulate Matter		Φ
		Filtration Time Particulate Matter and Filtration Time		\$
				\$
		Micro-separometer Rating (11)		\$
		Fuel Systems Icing Inhibitor		\$
		Visual (Color)		\$
		Sulfides in Bottom Water Copper (CU)		\$ \$
SubCLIN	Product	<u>Task</u>	Est. Sample	<u>Price per task</u>
	JP5	Transportation	0	\$
	JP5	Vessel Sampling	0	\$
		1 0	_	
	JP5	Tank Sampling	0	\$

CI	IN	0042 -	Ludi	low	MA

Lab name and address:		S: • Name	Name of Lab Manager		
		• Lab P	thone Number		
		• Lab F	ax Number		
		side normal working hours (overtime): \$			
Normal	working hours	am pm Mon Fri. E	except Holidays		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	15	\$	
	JP8	B-2	0	\$	
	JP8	C	0	\$	
	JP8	Air Force One	UTE	\$	
	JP8	Individual	UTE	<del></del>	
	010	Workmanship	012	\$	
		Color, Saybolt		\$	
		Total Acid Number, mg KOH/gm		\$	
		Aromatics		\$	
		Sulfur, Total Percent		\$	
		Sulfur, Mercaptan		\$	
		Doctor Test		\$	
		Distillation		\$	
		Flash Point		\$	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Net Heat of Combustion		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Naphthalenes		\$	
		Cetane Index, Calculated		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$	
		Existent Gum		\$	
		Particulate Matter and Filtration Time		\$	
		Water Reaction, Interface Rating		\$	
		Water Separation Index		\$	
		Fuel Systems Icing Inhibitor		\$	
		Fuel Electrical Conductivity		\$	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$	
		Sulfides in Water		\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$	
<u>SubCLIN</u>	Product	<u>Task</u>	Est. Sample	Price per task	
	JP8	Transportation	15	\$	
			_		
	JP8	Vessel Sampling	0	\$	
	JP8	Tank Sampling	0	\$	

CI	IN	0043 -	Andrews	$\Delta$ FR	MD
$\sim$ L	711 N	UU <del>1</del> J -	Anuicws	ALD.	. 1911

Lab name and address:		S: • Name of	Name of Lab Manager		
		• Lab Ph	one Number		
		• Lab Fa	x Number		
		side normal working hours (overtime): \$ am pm Mon Fri. Ex			
SubCLIN:	<u>Product</u>	Type of Test	Est.Sample	Price per tests/Series	
	JP8 JP8 JP8 JP8 JP8	B-1 B-2 C Air Force One Individual Workmanship Color, Saybolt Total Acid Number, mg KOH/gm Aromatics Sulfur, Total Percent Sulfur, Mercaptan Doctor Test Distillation Flash Point Density, or API Gravity Freezing Point Viscosity at -20°C Net Heat of Combustion Hydrogen Content Smoke Point Naphthalenes Cetane Index, Calculated Copper Strip Corrosion Thermal Stability Existent Gum Particulate Matter and Filtration Time Water Reaction, Interface Rating Water Separation Index Fuel Systems Icing Inhibitor Fuel Electrical Conductivity Color, Visual Particulate Matter (Solids) Filtration Time Sulfides in Water Copper (CU) Karl Fisher Water Water - AEL or Aqua-Glo	5 0 5 UTE UTE	\$	
<u>SubCLIN</u>	Product JP8	<u>Task</u> Transportation	Est. Sample 5	Price per task \$	
	JP8	Vessel Sampling	0	\$	
	JP8	Tank Sampling	0	\$	

## CLIN 0044 – Helena, AL

Lab name and address:		S: • Name o	Name of Lab Manager		
		• Lab Ph	one Number		
		• Lab Fa:	x Number		
Charge f	or working outs	side normal working hours (overtime): \$	per hour		
Normal	working hours	am pm Mon. – Fri. E	xcept Holidays		
SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series	
	JP8	B-1	1	\$	
	JP8	B-2	0	\$	
	JP8	C	0	\$	
	JP8	Air Force One	0	\$	
	JP8	Individual	UTE	<del></del>	
		Workmanship		\$	
		Color, Saybolt		\$	
		Total Acid Number, mg KOH/gm		\$	
		Aromatics		\$	
		Sulfur, Total Percent		\$	
		Sulfur, Mercaptan		\$	
		Doctor Test		\$	
		Distillation		\$	
		Flash Point		\$	
		Density, or API Gravity		\$	
		Freezing Point		\$	
		Viscosity at -20°C		\$	
		Net Heat of Combustion		\$	
		Hydrogen Content		\$	
		Smoke Point		\$	
		Naphthalenes		\$	
		Cetane Index, Calculated		\$	
		Copper Strip Corrosion		\$	
		Thermal Stability		\$	
		Existent Gum		\$	
		Particulate Matter and Filtration Time		\$	
		Water Reaction, Interface Rating		\$	
		Water Separation Index		\$	
		Fuel Systems Icing Inhibitor		\$	
		Fuel Electrical Conductivity		\$	
		Color, Visual		\$	
		Particulate Matter (Solids)		\$	
		Filtration Time		\$	
		Sulfides in Water		\$	
		Copper (CU)		\$	
		Karl Fisher Water		\$	
		Water - AEL or Aqua-Glo		\$	
SubCLIN	Product	<u>Task</u>	Est. Sample	Price per task	
	JP8	Transportation	0	\$	
	JP8	Vessel Sampling	0	\$	
	JP8	Tank Sampling	0	\$	

Lab hattle and address.	Name of Lab Manager
• Lab name and address:	<ul> <li>Name of Lab Manager</li> </ul>

Lab Phone Number
Lab Fax Number

Charge for working outside normal working hours (overtime): \$\_\_\_\_\_ per hour Normal working hours \_\_\_\_\_ am - \_\_\_\_ pm Mon. – Fri. Except Holidays

SubCLIN:	Product	Type of Test	Est.Sample	Price per tests/Series
	JP8	B-1	15	\$
	JP8	B-2	0	\$
	JP8	C	25	\$
	JP8	Air Force One	0	\$
	JP8	Individual	15	
		Workmanship		\$
		Color, Saybolt		\$
		Total Acid Number, mg KOH/gm		\$
		Aromatics		\$
		Sulfur, Total Percent		\$
		Sulfur, Mercaptan		\$
		Doctor Test		\$
		Distillation		\$
		Flash Point		\$
		Density, or API Gravity		\$
		Freezing Point		\$
		Viscosity at -20°C		\$
		Net Heat of Combustion		\$
		Hydrogen Content		\$
		Smoke Point		\$
		Naphthalenes		\$
		Cetane Index, Calculated		\$
		Copper Strip Corrosion		\$
		Thermal Stability		\$
		Existent Gum		\$
		Particulate Matter and Filtration Time		\$
		Water Reaction, Interface Rating		\$
		Water Separation Index		\$
		Fuel Systems Icing Inhibitor		\$
		Fuel Electrical Conductivity		\$
		Color, Visual		\$
		Particulate Matter (Solids)		\$
		Filtration Time		\$
		Sulfides in Water		\$
		Copper (CU)		\$
		Karl Fisher Water		\$
		Water - AEL or Aqua-Glo		\$

<u>SubCLIN</u>	<u>Product</u>	<u>Task</u>	Est. Sample	Price per task
	JP8	Transportation	50	\$
	JP8	Vessel Sampling	0	\$
	JP8	Tank Sampling	0	\$